

# LEATHER PROTECTORS

**Leather Protector Gloves** should always be worn over Rubber Insulating Gloves to provide the needed mechanical protection against cuts, abrasions and punctures. All Salisbury protectors are steamed pressed on curved hand forms to insure proper fit over Rubber Gloves. Manufactured from top grade leather, all are sewn with heavy duty nylon thread in the “gunn cut” inseam construction pattern. Each protector for Class 1-4 gloves are equipped with a nonmetallic buckle on the pull strap and an extra wide leather reinforcement over the thumb seam. Protectors for Class 00 and 0 gloves are available with non-metallic buckle and pull strap or elastic wrist.

**All Salisbury Leather Protectors meet ASTM F696 standards.**

It is the responsibility of the purchaser to specify the overall length of the protector gloves. The Clearance Table shows the minimum distance which shall be allowed between the protector glove cuff and the bead of the rubber glove per ASTM F496 Specifications.



**WARNING: Do not use leather protectors alone for protection against electric shock. Serious injury or death will result. Always use a properly rated insulating glove for the voltage being worked.**

Proper care of leather protectors is essential to user safety. Inspect the leather protectors when inspecting rubber gloves. Metal particles, imbedded wire, abrasive materials or any substance that could physically damage the rubber gloves must be removed from the protector before use.



**CLEARANCE TABLE FOR LEATHER PROTECTORS PER ASTM F496 - Table 4**

Glove Class	Min. Distance Between Protectors and Rubber Gloves	
	in.	mm
00, 0	1/2	13
1	1	25
2	2	51
3	3	76
4	4	102

Adapted, with permission, from F496-08 Standard Specification for In-Service Care of Insulating Gloves and Sleeves, copyright ASTM International, 100 Barr Harbor Drive, West Conshohocken, PA 19428. A copy of the complete standard may be obtained from ASTM, [www.astm.org](http://www.astm.org).

Minimum Distance from Protector and Rubber Glove	Glove Class	Leather Protector Cuff
		----- Cuff Line -----
	00, 0	1/2" from cuff
	1	1" from cuff
	2	2" from cuff
	3	3" from cuff
	4	4" from cuff

# PREMIUM LEATHER PROTECTORS

## SALISBURY ADVANTAGE

### 156 Premium Series

*Salisbury's SALCOR® cuff provides maximum protection.*

These protectors are made from specially tanned Grade A Red Boulevard buffed leather and an orange colored SALCOR “Super Cuff” in the 4” (102 mm) and 6” (152 mm) cuff lengths. The “Super Cuff” has better characteristics than leather or vinyl cuffs; it does not absorb water, has greater track resistance, and creepage.



Cat. No.	Cuff Length in. ( mm )	OAL Length in. ( mm )	Weight ea. lbs. ( kgs )
156-4	4 ( 102 ) Straight Cuff	12 ( 305 )	1 ( .5 )
156-6	6 ( 152 ) Straight Cuff	14 ( 356 )	1.2 ( .5 )

Available in dual sizes: 8/8.5, 9/9.5, 10/10.5, 11/11.5, 12



156-4



156-6

**SALISBURY** by Honeywell

# LEATHER PROTECTORS

## ILP Series

Manufactured from top grain cowhide, or goatskin, these protectors provide excellent protection for rubber insulating gloves at a very economical price. Cowhide cuffs are tough leather on palm side and orange vinyl on the back, while the goatskin cuffs are green leather on palm side and orange vinyl on back. Full complement of styles from low-volt through 16" contour cuff. Comes in size 7, dual sizes 8/8.5 through 11/11.5 and size 12.

## ILPM Series Mitten Protector

Manufactured from top grain cowhide, these protectors offer excellent comfort and protection. The ILPM Series mitten protectors feature adjustable straps with non-metallic buckles and are stitched with polyester thread for strong seams. Cuffs are tough leather on palm side and orange vinyl on the back of the hand. Comes in sizes 9, 10 and 11.

## LP Series

Manufactured from top grain cowhide or goatskin, these protectors offer excellent comfort and protection. The LP Series protectors feature adjustable straps with non-metallic buckles and are stitched with polyester thread for strong seams. Cuffs are tough leather on palm side and orange vinyl on the back of the hand. Comes in sizes 7 to 12, including half sizes 8 1/2 to 11 1/2.



ILPG10



ILPG10A



ILPM5S



ILP7C



LPG3S



LP7C



LPG5S

Cat. No.	OAL Length in. ( mm )	Weight ea. lbs. ( kgs )
----------	--------------------------	----------------------------

### ILP SERIES - COWHIDE

ILP3S*	12 ( 305 )	1 ( .5 )
ILP4S*	13 ( 330 )	1 ( .5 )
ILP5S*	14 ( 356 )	1.2 ( .5 )
ILP6S* / **	15 ( 381 )	1.2 ( .5 )
ILP7C* / **	16 ( 406 )	1.5 ( .7 )
ILP10*	10 ( 254 )	.7 ( .32 )
ILP10A* w/ pull strap	10 ( 254 )	.7 ( .32 )

\*To specify goatskin, use ILPG. Goatskin not available in size 7.

Available in dual sizes: 7, 8/8.5, 9/9.5, 10/10.5, 11/11.5, 12

\*\* Not available in size 7.

### ILPM SERIES - COWHIDE

ILPM3S	12 ( 305 )	1 ( .5 )
ILPM4S	13 ( 330 )	1 ( .5 )
ILPM5S	14 ( 356 )	1.2 ( .5 )

Available in sizes: 9, 10, 11

### LP SERIES

LP3S	12 ( 305 )	1 ( .5 )
LP4S	13 ( 330 )	1 ( .5 )
LP5S	14 ( 356 )	1.2 ( .5 )
LP6S	15 ( 381 )	1.2 ( .5 )
LP7C	16 ( 406 )	1.5 ( .7 )
LP10	10 ( 254 )	.7 ( .32 )
LP10A w/ pull strap	10 ( 254 )	.7 ( .32 )

To specify goatskin, use LPG.

Available in single sizes: 8, 8.5, 9, 9.5, 10, 10.5, 11, 11.5, 12