

# 15A 125V & 250V; 20A 125V & 250V



## Commercial Grade

2 YEAR LIMITED WARRANTY



ELECTRICAL		
DIELECTRIC VOLTAGE	CURRENT INTERRUPT.	TEMP. RISE
Withstands 2000V per UL 498	Full rated current	30°C max at full rated current after 100 cycles overload at 150% rated current for both AC and DC per UL 498

MECHANICAL		
TERMINAL I.D.	TERMINAL ACCOMM.	PRODUCT I.D.
Brass, hot Grounding White, neutral	#14 - #10 AWG	Ratings are permanently marked on device
ENVIRONMENTAL		
<b>FLAMMABILITY</b>	<b>OPERATING TEMP.</b>	
Rated V-2 per UL 94	-40°C to 60°C	

STANDARDS & CERTIFICATIONS					
NEMA WD6	ANSI C-73	UL 498	UL Fed Spec WC-596	CSA C22.2 No. 42	NOM
✓	✓	#E13399	-	#152105	#057
AC HORSEPOWER RATINGS					
15A 125V	15A 250V	20A 125V	20A 250V		
.5	1.5	1.0	2.0		

Side Wired



CR20-GY



5028



CR15S-GI



CR015-GY

FACE COLOR	DUPLEX RECEPTACLE	DUPLEX RECEPTACLE CANADIAN	DUPLEX RECEPTACLE TAMPER RESISTANT	DUPLEX RECEPTACLE SMOOTH FACE
<b>15A 125V, NEMA 5-15R, 2-P 3-W, Grounding</b>				
Brown Ivory White Gray Almond Black	CR15 CR15-I CR15-W CR15-GY CR15-A CR15-E	CR15-C CR15-CI	- CR15-SGI CR15-SGW	CR015 CR015-I CR015-W CR015-GY
<b>15A 250V, NEMA 6-15R, 2-P 3-W, Grounding</b>				
Brown Ivory	5028 5028-I	-	-	-
<b>20A 125V, NEMA 5-20R, 2-P 3-W, Grounding</b>				
Brown Ivory White Gray Almond Black	CR20 CR20-I CR20-W CR20-GY CR20-A CR20-E	-	-	CR020 CR020-I CR020-W CR020-GY
<b>20A 250V, NEMA 6-20R, 2-P 3-W, Grounding</b>				
Brown Ivory White	5822 5822-I 5822-W	-	-	-
FOR ADDITIONAL WALLPLATE OPTIONS SEE SECTION Q				

Commercial Grade Straight Blade Receptacles

B 19

