

## FEATURES & SPECIFICATIONS

**INTENDED USE** — Intended for low to medium mounting heights where dust, dirt, humidity, moisture, cold ambient spaces are present. Ideal for canopies, parking garages, dock areas, food processing facilities, car washes, schools, government facilities, stairwells, wastewater treatment and kitchen areas. **Certain airborne contaminants can diminish integrity of acrylic.**

[Click here for Acrylic Environmental Compatibility table for suitable uses.](#)

**CONSTRUCTION** — Housing formed from impact resistant, fiberglass reinforced polyester with cold-rolled steel enclosed wireway. Housing is self-extinguishing (ASTM D635-74). Poured in gasketing provides a seal between housing and diffuser. The gasketed inverted U-slot in housing provides a positive continuous seal between body and diffuser.

**FINISH** — Internal painted parts pretreated with a five-stage iron phosphate process to ensure superior paint adhesion and corrosion resistance, then finished with high-gloss baked white enamel.

**OPTICS** — High-impact Acrylic diffuser standard. Internal crepe pattern allows a smooth exterior surface for ease of cleaning. Diffuser flange fits snugly into the gasketed retention slot forming a continuous seal.

**ELECTRICAL** — Thermally protected, resetting, Class P, HPF, non PCB, UL listed and CSA Certified.

**INSTALLATION** — For unit or row installation. Surface mounting on ceiling or wall (horizontal on wall only). Suspended mounting by using chain or cable with supplied stainless steel spring mounting “U” bracket, (two per for 2’ and 4’ units). Gasketed wet location fittings on ends for feed through using rigid conduit.

**LISTING** — UL Listed and CSA Certified (standard) 347V is CSA Certified (standard). Listed for 25°C ambient (-20°F – 77°F) and wet locations (with approved mounting hardware) for covered ceiling applications. 2’ units IP67 rated. 4’ unit IP65 rated. Compliance to FDA/USDA requirements and/or NSF splash-zone certification.

**WARRANTY** — Fixtures, including ballast, are covered by Lithonia Lighting 24-month warranty against mechanical defects in manufacture.

Catalog Number
Notes
Type


Contractor Select

# Enclosed Industrial



2' and 4'

EGW



All dimensions are inches (centimeters).

### ORDERING INFORMATION

Catalog Number	UPC	Description	# of Lamps	Wattage	Voltage	Lamp Included	Pallet Qty.	Standard Carton Qty.
EGW217 MV	745976805968	2' Enclosed industrial fixture	2	17	120-277	N	64	1
EGW232 MV	745976806019	4' Enclosed industrial fixture	2	32	120-277	N	32	1

Accessories: Order as separate catalog number.	
DEGW24	2' Enclosed fixture replacement lens
DEGW48	4' Enclosed fixture replacement lens
DMW/EGW LATCH J6	2' and 4' Enclosed fixture replacement latch
EGWSMB	Replacement surface mounting bracket

