

Catalog Number	
Notes	Type

FEATURES & SPECIFICATIONS

INTENDED USE

For use with housings L7X, L7XR, L7PR, LC6, LCP, L7XF RECF.

CONSTRUCTION

Aluminum white sphere.
 Polyester powder coat paint.
 25 degree vertical tilt standard.
 White narrow integral flange.

INSTALLATION

Socket-to-trim interface.
 Retaining clips installed at factory to top of trim to hold trim inside housing.

LISTING


U.L. Listed to U.S. and Canadian safety standards.
 Damp location listed.

6" Full Reflector Trim

7E1



STANDARD EYEBALL
Wide Flange



Specifications

Height: 4 (10.2)
 Lamp Opening: 4-7/8 (12.4)
 Diameter: 7-5/8 (19.4)

All dimensions are inches (centimeters) unless otherwise specified.

ORDERING INFORMATION

Example: **7E1**

Choose the boldface catalog nomenclature that best suits your needs and write it on the appropriate line. Order accessories as separate catalog number.

7E1	
Series	Finish
7E1	(blank) White eyeball

Housing Compatibility

Housing and trim ordered separately.

<i>Application</i>	<i>Source</i>	<i>Maximum wattage</i>	<i>Housing</i>
<i>IC</i>	Incandescent	75 PAR30	L7X, L7XR, L7PR, LC6, LCP
		65 BR30	L7X, L7XR, L7PR, LC6, LCP
	Fluorescent	18 TRT	L7XF RECF

7E1 6" Standard Eyeball Full Reflector Trim

