

Catalog Number	
Notes	Type

## FEATURES & SPECIFICATIONS

### INTENDED USE

For use with frame-in LP6 and housings LI6, LI6F, LI6F RECF.

### CONSTRUCTION

Aluminum white polyester powder coat painted.

One piece reflector.

White integral flange.

Adjustable socket plate allows lamp to align perpendicular to the floor.

Accommodates ceiling pitch ranging from 2/12 to 12/12.

Maximum ceiling thickness 1-1/2".

### INSTALLATION

Socket to trim interface.

Rough-ins with clips retain trims.

### LISTING


U.L. Listed to U.S. and Canadian safety standards.

Damp location listed.

Patent # 5,452,193.

6" Full Reflector Trim

# 6S01



**SLOPED OPEN**  
Narrow Flange


### Specifications

Height: 7-1/4 (18.4)

Lamp Opening: 6-1/4 (15.9)

Diameter: 8-1/4 (20.9)

Trim height when used with  
Non-IC incandescent rough-in



All dimensions are inches (centimeters).

## ORDERING INFORMATION

Choose the boldface catalog nomenclature that best suits your needs and write it on the appropriate line.

Example: **6S01**

**6S01**

<b>Series</b>	<b>Finish</b>
6S01	(blank) White

### Housing Compatibility

Housing and trim ordered separately.

<i>Application</i>	<i>Source</i>	<i>Maximum wattage</i>	<i>Housing</i>
<i>IC</i>	Incandescent	100 PAR38	<b>LI6</b>
		75 PAR30	<b>LI6</b>
		85 BR40	<b>LI6</b>
		65 BR30	<b>LI6</b>
	Fluorescent	26 TRT	<b>LI6F RECF</b>
		32 TRT	<b>LI6F</b>
<i>Non-IC</i>	Incandescent	150 PAR38	<b>LP6</b>
		75 PAR30	<b>LP6</b>
		120 BR40	<b>LP6</b>
		65 BR30	<b>LP6</b>
		100 A19	<b>LP6</b>

# 6S01 6" Sloped Open Full Reflector Trim

---

For photometric data consult factory.

Consult chart on page **LAMP** for appropriate R or PAR lamp data.



## Lithonia Lighting

Acuity Lighting Group, Inc.

Recessed Downlighting

One Lithonia Way, Conyers, GA 30012

Phone: 800-315-4935 Fax: 770-860-3106

In Canada: 160 avenue Labrosse, Pointe-Claire, P.Q. H9R 1A1  
[www.lithonia.com](http://www.lithonia.com)