

Technical data sheet -

Cable fittings and accessories

Identification	Type Part-No.	TOP-T Locknuts Plastic NPT 3/4" LPNPT34G
Use/Application/Characteristics		
Characteristics	<ul style="list-style-type: none">• Hexagonal locknut for secure tightening of plastic cable, fittings and accessories• Easy to install	
Technical data		
Temperature range	-20 °C ... +100 °C -4 °F ... +212 °F	
max. short-time temperature up to	+150 °C / +300 °F	
Outer Ø	37.5 mm	
Thread form	NPT	
Thread G	NPT 3/4"	
SW	33 mm	
H	6 mm	
Construction		
Material	PA 6 GF 30	
Color	grey RAL 7001	
General		
Note	Flange is imprinted with locknut size for easy identification.	

27.10.2018 – Subject to technical modification

Part-No. LPNPT34G

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY