

Preset dimmers



- Button turns on/off to slider level
- Slide up to brighten, down to dim
- Loads from 1000-1500 watts require large controls



Incandescent/halogen dimmers

(small controls)

Preset dimmers

3-way/single-pole 120V 600W	NT-603P- XX ¹
3-way/single-pole 120V 1000W	NT-1003P- XX ¹



Magnetic low-voltage dimmers

(small controls)

Preset dimmers

3-way/single-pole (small) 120V 600VA (450W)	NTLV-603P- XX ¹
3-way/single-pole (small) 120V 1000VA (800W)	NTLV-1003P- XX ¹

The stated VA (Volt-Ampere) rating includes the magnetic transformer heat losses and the lamp load. The stated W (Watt) rating is the maximum lamp wattage based on assumed 20% transformer loss.

3-wire fluorescent dimmers*

(also for Hi-lume[®] A-Series LED drivers)
(small controls)

Preset dimmers

3-way 120V 8A	NTF-103P- XX ¹
3-way 277V 6A	NTF-103P-277- XX ¹

For use with EcoSystem[®], Hi-lume 3D and Hi-lume ballasts, and Hi-lume A-Series LED drivers.

No derating required if ganged.

Adjustable low-end trim.

For more information on Hi-lume A-Series LED drivers, visit www.lutron.com/HilumeLED.

To control lights from multiple-locations, use 3-way dimmer with NT-3PS- and NT-4PS- or other mechanical switches.

XX¹: Architectural matte color codes, see pg. 26 (1-gang wallplate included)

All models must be derated if ganged, unless otherwise noted, see pg. 179.

* Requires neutral wire connection.