

T5 Linear

EcoSystem® H-Series (1% or less dimming) universal voltage digital dimming ballasts

- Architectural dimming to 1% or less
- Compatible with Lutron EcoSystem digital controls
- Energy saving and cost-effective

Lamp Watts (Length)	Lamps per Ballast	Model Number	Case Type*	Input Voltage (VAC)	Input Current (A)	Input Power (W)	Ballast Factor (BF)**	System Lumens (lm) [†]	System Efficacy (lm/W) [†]	Ballast Efficacy Factor (BEF)	Relative System Efficacy (RSE)		
28W (45.2 in)	1	EHD T528 C U 1 10	C	277	0.12	32.6	1.00	2,900	89	3.07	0.86		
				240	0.14	32.9	1.00	2,900	88	3.04	0.85		
				120	0.27	32.9	1.00	2,900	88	3.04	0.85		
	2	EHD T528 C 347 1 10	C	347	0.09	30.9	1.00	2,900	94	3.23	0.91		
				EHD T528 C U 2 10	C	277	0.23	64.5	1.00	5,800	90	1.55	0.87
						240	0.27	65.0	1.00	5,800	89	1.54	0.86
		EHD T528 C 347 2 10	C	120	0.54	65.2	1.00	5,800	89	1.53	0.86		
			C	347	0.17	58.4	1.00	5,800	99	1.71	0.96		

*For case type information see pages 42 and 43.

**Factory-tuned ballast factors available. To customize visit www.lutron.com/BallastTool.

[†]Actual number may vary with lamp model. Please consult the lamp manufacturer for lamp-specific data.