



SINGLE POSITION

125 & 200 AMP-5 TERMINAL-JAW CLAMPING LEVER BYPASS-RINGLESS-600 VAC

125 AMP-5 TERMINAL-RINGLESS-1Ø3W

CATALOG NUMBER	SERVICE	HUB	CONNECTORS CU/AL	BY-PASS	DIMENSIONS			CONCENTRIC K.O.'S					
					D"	W"	H"	1	2	3	4	5	6
U3505-XL-TG-HSP	OH/UG	C.P.	#6 - 2/0	LEVER	4 ⁷ / ₈	10	18 ¹ / ₂	2	2	2	2	¼	¼, ½
UAP3505-XL-TG-HSP	OH/UG	C.P.	#6 - 2/0	LEVER	4 ⁷ / ₈	10	18 ¹ / ₂	2	2	2	2	¼	¼, ½

200 AMP-5 TERMINAL-RINGLESS-1Ø3W & 3Ø3W

CATALOG NUMBER	SERVICE	HUB	CONNECTORS CU/AL	BY-PASS	DIMENSIONS			CONCENTRIC K.O.'S					
					D"	W"	H"	1	2	3	4	5	6
U9550-RRL-QG-HSP	OH	H.O.	#6-350 kcmil	LEVER	4 ⁷ / ₈	10	18 ¹ / ₂	3	2 ¹ / ₂	3	—	¼, ½	¾
U9551-X-QG-HSP	OH/UG	C.P.	#6-350 kcmil	LEVER	4 ⁷ / ₈	13	19	3	2 ¹ / ₂	3	3	¼	¼, ½
UAP9551-X-QG-HSP	OH/UG	C.P.	#6-350 kcmil	LEVER	4 ⁷ / ₈	13	19	3	2 ¹ / ₂	3	3	¼	¼, ½
U3296-X-HSP	OH/UG	C.P.	¾"-16 STUD	LEVER	4 ⁷ / ₈	13	28 ¹ / ₄	3	3	3	3	¼	¼, ½
UAP3296-X-HSP	OH/UG	C.P.	¾"-16 STUD	LEVER	4 ⁷ / ₈	13	28 ¹ / ₄	3	3	3	3	¼	¼, ½

ALUMINUM CONSTRUCTION: To order an aluminum meter socket rather than steel, change the catalog number prefix from -U to -UAP. This designates an aluminum, painted meter socket.

HUBS: For proper hub selection, see hub suffix chart on accessory page.

CONNECTORS: Extruded aluminum connectors are tin plated. For the **U3296-X** stud-type unit, order connector kits separately. Order 2 kits to cover both line and load side: **K1539** (350 kcmil) or **K1540** (600 kcmil.) See accessory page.

BYPASS: Lever supplies clamping action on meter spades and also operates bypass device.