

EXD-Q-3

([Home](#) : [Products](#) : [Switches](#) : [MICRO SWITCH™ Hazardous Location Switches](#) : [EX](#))



Explosion-Proof Limit Switches Series EX: Top Plunger; 2NC 2NO DPDT Snap Action; 3 foot Cable

Actual product appearance may vary.

[Sales & Service](#)

[Distributor Inventory](#)

[Overview](#)

[Specs](#)

[Documentation](#)

Product Specifications

Availability	Global
Operating Force (OF)	13,34 N [3.0 lb] max.
Pretravel (PT)	3,96 mm [0.156 in] max.
Overtravel (OT)	3,54 mm [0.141 in] min.
Differential Travel (DT)	1,52 mm [0.060 in] max.
Product Type	MICRO SWITCH™ Explosion-Proof Limit Switches
Actuator	Top Plunger
Circuitry	2NC 2NO DPDT Snap Action
Ampere Rating	10 A Ind./0.3 A Res./0.15 A Res.
Supply Voltage	125 Vac, 250 Vac/125 Vdc/250 Vdc
Housing Material	Aluminum
Termination Type	0,91 m (3 ft.) Leadwires
Housing Type	EX
Series Name	EX
Sealing	NEMA 1, 7 (Class I, Division 1, Groups B, C, D), 9 (Class II, Division 1, Groups E, F, G)
CSA File #	LR57324
UL File #	E14274
ATEX File #	KEMA 04ATEX2312 X
IEC Ex	Yes
Operating Temperature	-40 °C to 71 °C [-40 °F to 160 °F]
Comment	Preleded with 0,91 m (3 ft.) leadwire
Agency	

Standards

UNSPSC Code 39122213

UNSPSC Commodity 39122213 Limit Switch

Sealed Explosion-proof

Unit Packaging-Net Weight 773 1705

Unit Packaging-Height 114.06 MM

Unit Packaging-Width 51.1 MM

Unit Packaging-Length 93 MM

Description MICRO SWITCH™ Hazardous Location Switches: EX Series Explosion-Proof Limit Switch, Pin Plunger Actuator, 2NC - 2NO Double Pole Double Throw (DPDT), Snap Action, Furnished with 36 inch Lead Wire, Class I, Group B (hydrogen atmospheres)

Static Sensitive No

RoHS Compliant Compliant

Product Line Hazardous Location Switches

HTS Code 8536509040

UPC Code 78454924455

Country of Origin US

Exp. Ctrl Class (ECCN) EAR99

WEEE Compliance 4

Please Note: The trade data (Export Classification, Tariff Number and Country of Origin) provided is believed to be accurate and represents the best information currently available to Honeywell. However Honeywell makes no warranty, expressed or implied with respect to accuracy of the trade data and Honeywell assumes no liability resulting from your use of the trade data. Your use of the trade data provided by Honeywell is at your own risk. You may be legally required to make your own investigations to determine the suitability of the trade data for your intended purposes. In no way shall Honeywell be liable for any claims, losses or damages from the trade data.