

Armorlite® Type MC Multi-Circuit



14 AWG through 10 AWG Copper THHN/THWN Insulated Singles. Multiple Circuits. Green Insulated Grounding Conductor. UL Listed. 600 Volts. Rated VW-1. Lightweight Aluminum Interlocked Armor.

APPLICATIONS

Southwire Armorlite® Type MC Cable - Multi-Circuit is suitable for use as follows:

- Multiple circuits for branch, feeder and service power distribution in commercial, industrial, institutional, and multi-residential buildings.
- Fished or embedded in plaster.
- Concealed or exposed installations.
- Environmental air-handling spaces per NEC 300.22 (C).
- Places of Assembly per NEC 518.4 and theaters per NEC 520.5.
- Installation in cable tray and approved raceways.
- Under raised floors for information technology equipment conductors and cables per NEC 645.5(D) & 645.5(D)(2).
- Class I Div. 2, Class II Div 2, & Class III Div. 1 Hazardous Locations.

STANDARDS & REFERENCES

Southwire's Armorlite® Type MC Cable - Multi-Circuit meets or exceeds the following requirements:

- UL 83
- UL 1569
- UL 1685
- UL Online Product Guide Info - Metal-Clad Cable (PJAZ) (www.ul.com)
- Federal Specification A-A59544 (formerly J-C-30B)
- NFPA 70 (National Electrical Code), Article 330
- Listed for use in UL 1, 2 and 3 Hour Through Penetration Firestop Systems
- Jacketed & Non Jacketed will both pass " UL Test" & "FT4/IEEE 1202" (70,000 Btu/hr) Vertical Cable Tray Flame Test
- REACH/RoHS-2 (Chemical Limit) Compliant

CONSTRUCTION

Southwire Armorlite® Type MC Cable - Multi-Circuit is constructed with 14 awg through 10 awg soft-drawn copper Type THHN/THWN conductors rated 90°C dry, and a green insulated grounding conductor. The conductors are cabled together and a binder tape bearing the print legend is wrapped around the assembly. Aluminum interlocking armor is applied over the assembly. An optional PVC jacket can be applied over the armored assembly.



The Power of Connections.™



Southwire®

©2016 Southwire Company, LLC. All rights reserved. *Registered Trademark of Southwire Company, LLC.
One Southwire Drive, Carrollton, GA 30119, USA

| CONDUCTOR SIZE AND COLORS | GROUNDING SIZE AND COLOR | STOCK NUMBER | | WEIGHT (LBS/1000') | OVERALL DIAMETER (INCHES) |
|---|--------------------------|-----------------------|------------------------|--------------------|---------------------------|
| SOLID CONDUCTOR COLORS 120/208V | | | | | |
| 12-6 SOLID (BLACK/BLACK-WHITE/WHITE/WHITE-BLACK/RED/RED-WHITE) | 12 SOLID (GREEN) | 69-00-57-01 (250') | 69-00-57-03 (1000') | 205 | .574 |
| 12-8 SOLID (BLACK/BLACK-WHITE/WHITE/WHITE-BLACK/RED/RED-WHITE/BLUE/BLUE-WHITE) | 12 SOLID (GREEN) | 69-00-65-01 (250') | 69-00-65-03 (1000') | 256 | .647 |
| 12-12 SOLID (BLACK/BLACK-WHITE/WHITE/WHITE-BLACK/RED/RED-WHITE/BLUE/BLUE-WHITE/BLACK-RED/RED-BLACK/BLUE-RED/WHITE-RED) | 12 SOLID (GREEN) | 69-00-73-02 (500') | 69-00-73-03 (1000') | 379 | .742 |
| 10-6 SOLID (BLACK/BLACK-WHITE/WHITE/WHITE-BLACK/RED/RED-WHITE) | 10 SOLID (GREEN) | 55-29-70-02 (500') | 55-29-70-03 (1000') | 307 | .668 |
| 10-8 SOLID (BLACK/BLACK-WHITE/WHITE/WHITE-BLACK/RED/RED-WHITE/BLUE/BLUE-WHITE) | 10 SOLID (GREEN) | 69-00-81-02 (500') | 69-00-81-03 (1000') | 416 | .80 |
| 10-12 SOLID (BLACK/BLACK-WHITE/WHITE/WHITE-BLACK/RED/RED-WHITE/BLUE/BLUE-WHITE/BLACK-RED/RED-BLACK/BLUE-RED/WHITE-RED) | 10 SOLID (GREEN) | 55-29-86-03 (500') | 55-29-86-02 (1000') | 571 | .879 |
| STRANDED CONDUCTOR COLORS 120/208V | | | | | |
| 12-6 STRANDED (BLACK/BLACK-WHITE/WHITE/WHITE-BLACK/RED/RED-WHITE) | 12 STRANDED (GREEN) | 55-13-53-02 (500') | 55-13-53-03 (1000') | 218 | .602 |
| 12-8 STRANDED (BLACK/BLACK-WHITE/WHITE/WHITE-BLACK/RED/RED-WHITE/BLUE/BLUE-WHITE) | 12 STRANDED (GREEN) | 55-13-54-04 (500') | 55-13-54-03 (1000') | 273 | .680 |

| | | | | | |
|--|------------------------|-----------------------|------------------------|-----|------|
| 12-12 STRANDED (BLACK/BLACK- WHITE/WHITE/WHITE- BLACK/RED/RED- WHITE/BLUE/BLUE- WHITE/BLACK-RED/RED- BLACK/BLUE-RED/WHITE-RED) | 12 STRANDED (GREEN) | 55-13-55-02 (500') | 55-13-55-03 (1000') | 403 | .782 |
| 10-6 STRANDED (BLACK/BLACK- WHITE/WHITE/WHITE- BLACK/RED/RED-WHITE) | 10 STRANDED (GREEN) | | 55-32-38-03 (1000') | 345 | .701 |
| 10-8 STRANDED (BLACK/BLACK- WHITE/WHITE/WHITE- BLACK/RED/RED- WHITE/BLUE/BLUE-WHITE) | 10 STRANDED (GREEN) | 55-13-56-02 (500') | 55-13-56-03 (1000') | 437 | .799 |
| Consult NEC Section 310.15 for ampacities. | | | | | |

FEATURES

- Reduces installation costs up to 50% over pipe and wire.
- UL Classified 1, 2, and 3 hour Through Penetration Firestop Systems: W-J-3037, W-L-3110, W-L-3113, W-L-3117, W-L-3120, W-L-3121, W-L-3160, C-AJ-3115, C-AJ-3140, C-AJ-3142, C-AJ-3145, C-AJ-3173, C-AJ-3202, C-AJ-4065, C-AJ-4066, F-C-3038.
- Cable reverse wound on reel for ease of pulling and installation. When pulling from coils, pull from inside to ensure ease of installation.
- Anti-short bushings are not required for use with MC cable per the NEC and UL

| 6 CONDUCTOR W/ GROUND | 8 CONDUCTOR W/ GROUND | 12 CONDUCTOR W/ GROUND |
|-----------------------|-----------------------|------------------------|
| BLACK | BLACK | BLACK |
| RED | RED | RED |
| WHITE | BLUE | BLUE |
| BLACK W/ WHITE STRIPE | WHITE | WHITE |
| RED W/ WHITE STRIPE | BLACK W/ WHITE STRIPE | BLACK W/ WHITE STRIPE |
| WHITE W/ BLACK STRIPE | RED W/ WHITE STRIPE | RED W/ WHITE STRIPE |
| GREEN GROUND | BLUE W/ WHITE STRIPE | BLUE W/ WHITE STRIPE |
| | WHITE W/ BLACK STRIPE | WHITE W/ BLACK STRIPE |
| | GREEN GROUND | BLACK W/ RED STRIPE |
| | | RED W/ BLACK STRIPE |
| | | BLUE W/ RED STRIPE |
| | | WHITE W/ RED STRIPE |
| | | GREEN GROUND |

The Power of Connections.™



NEC TABLE 310.15(B)(16)- ALLOWABLE AMPACITY FOR 600V CONDUCTORS

| SIZE AWG OR KCMIL | TEMPERATURE RATING OF CONDUCTOR | | |
|--|---------------------------------|---|---|
| | 60°C (140°F) | 75°C (167°F) | 90°C (194°F) |
| | Types: TW, UF | Types: RHW, THHW, THW, THWN, XHHW, USE, ZW | Types: TBS, SA, SIS, RHH, RHW-2, THHN, THHW, THW-2, THWN- 2, USE-2, XHH, XHHW, XHHW-2, ZW-2 |
| COPPER | | | |
| 18 | - | - | 14 |
| 16 | - | - | 18 |
| 14 | 15 | 20 | 25 |
| 12 | 20 | 25 | 30 |
| 10 | 30 | 35 | 40 |
| 8 | 40 | 50 | 55 |
| 6 | 55 | 65 | 75 |
| 4 | 70 | 85 | 95 |
| 3 | 85 | 100 | 115 |
| 2 | 95 | 115 | 130 |
| 1 | 110 | 130 | 145 |
| 1/0 | 125 | 150 | 170 |
| 2/0 | 145 | 175 | 195 |
| 3/0 | 165 | 200 | 225 |
| 4/0 | 195 | 230 | 260 |
| 250 | 215 | 255 | 290 |
| 300 | 240 | 285 | 320 |
| 350 | 260 | 310 | 350 |
| 400 | 280 | 335 | 380 |
| 500 | 320 | 380 | 430 |
| 600 | 350 | 420 | 475 |
| 700 | 385 | 460 | 520 |
| 750 | 400 | 475 | 535 |
| 800 | 410 | 490 | 555 |
| 900 | 435 | 520 | 585 |
| 1000 | 455 | 545 | 615 |
| 1250 | 495 | 590 | 665 |
| 1500 | 525 | 625 | 705 |
| 1750 | 545 | 650 | 735 |
| 2000 | 555 | 665 | 750 |
| Per NEC 310.15(B)(5), the ampacity of 4/C cables shall be reduced by a factor of 0.80 when the neutral is considered a current-carrying conductor. | | | |

Table is reprinted from NFPA 70-2014, the National Electric Code, © 2013 National Fire Protection Association, Quincy, Massachusetts 02269. This reprinted material is not the complete and official position of the National Fire Protection Association on the referenced subject, which is represented only by the standard in its entirety.