

# Factory bent to save time and materials!

## OCAL-BLUE Standard-Radius Elbows


- Fabricated from Ocal™ PVC-coated conduit.
- Standard radius in 30°, 45°, 60° and 90° available for immediate shipment.
- Colour-coded thread protectors for easy identification of conduit size.
- Special radius and degrees not listed are also available upon request.



File #110787

| Cat. No.    |                  | Pipe Size  | Radius "R"     | Offset "C"     | Straight End "D" | Unbent Length   | Weight Each Steel Only |
|-------------|------------------|------------|----------------|----------------|------------------|-----------------|------------------------|
| Steel       | Aluminum         | in. (mm)   | in. (mm)       | in. (mm)       | in. (mm)         | in. (mm)        | lb. (kg)               |
| ELL1/2-_-   | ELL1/2-_-SA-_-   | 1/2 (16)   | 4.00 (101.60)  | 6.00 (152.40)  | 2.00 (50.80)     | 10.28 (261.19)  | 0.67 (16.95)           |
| ELL3/4-_-   | ELL3/4-_-SA-_-   | 3/4 (21)   | 4.50 (114.30)  | 6.50 (165.10)  | 2.00 (50.80)     | 11.07 (281.14)  | 0.95 (24.07)           |
| ELL1-_-     | ELL1-_-SA-_-     | 1 (27)     | 5.75 (146.05)  | 8.00 (203.20)  | 2.25 (57.15)     | 13.53 (343.71)  | 1.77 (44.97)           |
| ELL1-1/4-_- | ELL1-1/4-_-SA-_- | 1-1/4 (35) | 7.25 (184.15)  | 9.50 (241.30)  | 2.25 (57.15)     | 15.89 (403.56)  | 2.55 (64.80)           |
| ELL1-1/2-_- | ELL1-1/2-_-SA-_- | 1-1/2 (41) | 8.25 (209.55)  | 11.00 (279.40) | 2.75 (69.85)     | 18.46 (468.86)  | 3.98 (101.13)          |
| ELL2-_-     | ELL2-_-SA-_-     | 2 (53)     | 9.50 (241.30)  | 13.00 (330.20) | 3.50 (88.90)     | 21.92 (556.83)  | 6.33 (160.86)          |
| ELL2-1/2-_- | ELL2-1/2-_-SA-_- | 2-1/2 (63) | 10.50 (266.70) | 14.00 (355.60) | 3.50 (88.90)     | 23.49 (596.73)  | 9.65 (245.09)          |
| ELL3-_-     | ELL3-_-SA-_-     | 3 (78)     | 13.00 (330.20) | 16.50 (419.10) | 3.50 (88.90)     | 27.42 (696.48)  | 15.42 (391.77)         |
| ELL3-1/2-_- | ELL3-1/2-_-SA-_- | 3-1/2 (91) | 15.00 (381.00) | 20.75 (527.05) | 5.75 (146.05)    | 35.06 (890.57)  | 23.30 (591.84)         |
| ELL4-_-     | ELL4-_-SA-_-     | 4 (103)    | 16.00 (406.40) | 21.75 (552.45) | 5.75 (146.05)    | 36.63 (930.47)  | 29.68 (753.80)         |
| *ELL5-_-    | ELL5-_-SA-_-     | 5 (129)    | 24.00 (609.60) | 31.00 (787.40) | 7.00 (177.80)    | 51.70 (1313.16) | 60.82 (1544.89)        |
| *ELL6-_-    | ELL6-_-SA-_-     | 6 (155)    | 30.00 (762.00) | 39.00 (990.60) | 9.00 (228.60)    | 65.12 (1654.15) | 85.69 (2176.51)        |

Metric size designator (ANSI C80.1-1994).  
\*Not CSA certified.



| Cat. No.        | Pipe Size | Angle       | Material      | Colour           |
|-----------------|-----------|-------------|---------------|------------------|
| <b>ELL 3/4-</b> | -         | -           | -             | -                |
|                 |           | 30 = 30°    | Blank = Steel | <b>G</b> = Grey  |
|                 |           | 45 = 45°    | SA = Aluminum | <b>W</b> = White |
|                 |           | 60 = 60°    |               | <b>B</b> = Blue  |
|                 |           | Blank = 90° |               | <b>R</b> = Red   |

**Catalogue No. Example:**  
ELL3/ASA-W is a 3/4" trade size 90° aluminum elbow coated in white PVC.

*Custom colours also available - Std. min. quantities are required. Please contact your Regional Sales Office.*

Ocal™ Corrosion Protection for Electrical Conduit and Fittings