

SAFETY, FACILITY & EQUIPMENT
IDENTIFICATION

BradyID.com/s35

Your experts
for safety,
facility and
equipment
identification.



Inside-Panel Component Labels for Electrical, Automation and Data Centers (B-422, B-428, B-483, B-499 and B-595)

Variety of durable materials ideal for marking backer boards, DIN rail, relays, PLCs, switches and solenoids. Create serial or rating plates with barcodes, graphics and more with a flexible high-tack adhesive for easy and long-lasting adhesion.

- B-422 Polyester Material** - Permanent adhesive, good for powder-coated/textured surfaces. Best on flat surfaces. Temp. range: -40°F to 212°F (-40°C to 100°C). UL recognized.
- B-428 Metalized Polyester Material** - Permanent adhesive, silver finish. Temp. range: -40°F to 176°F (-40°C to 80°C). UL recognized.
- B-483 Polyester Material** - Permanent adhesive for powder-coated/textured surfaces. Best on flat surfaces. Temp. range: -40°F to 248°F (-40°C to 120°C). UL recognized.
- B-499 Nylon Cloth Material** - Permanent adhesive. Pliable for rough or smooth surfaces. Temp. range: -94°F to 194°F (-70°C to 90°C). UL recognized.
- B-595 Indoor/Outdoor Vinyl Material** - Permanent adhesive, very pliable, good for rough surfaces and outdoor use, wide range of colors. Temp. range: -40°F to 180°F (-40°C to 82°C). UL recognized.




Figure 29



Figure 33




Figure 46 (with border)

Fits Printer Model	Diagram	Catalog #	B#	Material	Color	Label Width A Inch (mm)	Label Height B Inch (mm)	Labels/Roll	Ribbon in Cartridge
B-422 – Gloss Polyester									
BMP41, 51, 53	Fig. 33	MC-375-422	B-422	Gloss Polyester	BK on WT	0.375 (9.5)	25 ft (7.6 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-475-422	B-422	Gloss Polyester	BK on WT	0.475 (12.1)	25 ft (7.6 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-500-422	B-422	Gloss Polyester	BK on WT	0.500 (12.7)	25 ft (7.6 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 29	M-7-422	B-422	Gloss Polyester	BK on WT	0.500 (12.70)	0.500 (12.70)	280	R6000
BMP41, 51, 53	Fig. 29	M-89-422	B-422	Gloss Polyester	BK on WT	0.500 (12.70)	1.500 (38.10)	360	R6000
BMP41, 51, 53	Fig. 29	M-47-422	B-422	Gloss Polyester	BK on WT	1.000 (25.40)	0.500 (12.70)	360	R6000
BMP41, 51, 53	Fig. 29	M-49-422	B-422	Gloss Polyester	BK on WT	1.000 (25.40)	1.000 (25.40)	200	R6000
BMP41, 51, 53	Fig. 33	MC1-1000-422	B-422	Gloss Polyester	BK on WT	1.000 (25.40)	25ft. (7.62m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 29	M-90-422	B-422	Gloss Polyester	BK on WT	1.500 (38.10)	0.750 (19.05)	200	R6000
B-428 – Metalized Polyester									
BMP51, 53	Fig. 29	M-29-428	B-428	Metalized Polyester	Lt. Grey	0.500 (12.70)	1.500 (38.10)	360	R4300
BMP51, 53	Fig. 29	M-30-428	B-428	Metalized Polyester	Lt. Grey	0.750 (19.05)	1.500 (38.10)	260	R4300
BMP41, 51, 53	Fig. 29	M-47-428	B-428	Metalized Polyester	Lt. Grey	1.000 (25.40)	0.500 (12.70)	360	R4300
BMP41, 51, 53	Fig. 46	M-92-428-BB	B-428	Metalized Polyester	Lt. Grey	1.130 (28.70)	0.500 (12.70)	360	R4300
BMP41, 51, 53	Fig. 29	M-60-428	B-428	Metalized Polyester	Lt. Grey	2.000 (50.80)	1.000 (25.40)	80	R4300
B-483 – Ultra Aggressive Polyester									
BMP41, 51, 53	Fig. 29	M-47-483	B-483	Polyester	BK on WT	1.000 (25.4)	0.500 (12.7)	480	R6000
BMP41, 51, 53	Fig. 29	M-61-483	B-483	Polyester	BK on WT	2.000 (50.80)	0.500 (12.70)	80	R6000
BMP41, 51, 53	Fig. 29	M-60-483	B-483	Polyester	BK on WT	2.000 (50.80)	1.000 (25.40)	80	R6000
B-499 – Nylon Cloth									
BMP41, 51, 53	Fig. 29	M-131-499	B-499	Nylon Cloth	BK on WT	0.500 (12.7)	1.000 (25.40)	180	R4300
BMP41, 51, 53	Fig. 29	M-11-499	B-499	Nylon Cloth	BK on WT	0.500 (12.70)	0.750 (19.05)	220	R4300
BMP41, 51, 53	Fig. 29	M-84-499	B-499	Nylon Cloth	BK on WT	0.900 (22.86)	0.500 (12.70)	200	R4300
BMP41, 51, 53	Fig. 29	M-128-499	B-499	Nylon Cloth	BK on WT	1.000 (25.40)	1.900 (48.3)	100	R4300
BMP51, 53	Fig. 29	M-132-499	B-499	Nylon Cloth	BK on WT	1.500 (38.10)	1.250 (31.75)	160	R4300
B-595 – Indoor / Outdoor Vinyl Tape*									
BMP41, 51, 53	Fig. 33	MC-500-595-WT-BK	B-595	Vinyl	BK on WT	0.500 (12.70)	25 ft. (7.62 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC1-1000-595-WT-BK	B-595	Vinyl	BK on WT	1.000 (25.40)	25 ft. (7.62 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-500-595-YL-BK	B-595	Vinyl	BK on YL	0.500 (12.70)	25 ft. (7.62 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC1-1000-595-YL-BK	B-595	Vinyl	BK on YL	1.000 (25.40)	25 ft. (7.62 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-500-595-OR-BK	B-595	Vinyl	BK on OR	0.500 (12.70)	25 ft. (7.62 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC1-1000-595-OR-BK	B-595	Vinyl	BK on OR	1.000 (25.40)	25 ft. (7.62 m)	1 roll (cont.)	R6000

* For additional vinyl label colors, refer to the B-595 Indoor/Outdoor Grade Facility and Safety Labels on page 326.