

Aluminum Entrance Caps

Type ECO

Clamp-on Aluminum

Use:

Clamp type weather resistant aluminum entrance caps for threaded or unthreaded rigid conduit, IMC or EMT service masts.

Material/Finish:

Aluminum/Natural

Third Party Certification:


 UL Listed: E-163167

Applicable Third Party Standards:


UL Standard: 514B
NEMA: FB-1

Trade Size (inches)	Catalog Number	Dimensions in Inches		No. Holes	Size Holes
		A	B		
1/2	ECO-100*	2.70	3.25	4	19/64
3/4	ECO-101*	2.80	3.64	2	3/8
				3	19/32
1	ECO-102	3.40	4.15	2	7/16
				3	1/2
1 1/4	ECO-103	3.32	4.61	2	27/64
				3	5/8
1 1/2	ECO-104	4.75	5.79	2	19/32
				1	7/16
				3	3/4
2	ECO-105	5.75	6.90	2	3/4
				3	1
				1	1 1/16
2 1/2	ECO-106	7.00	10.50	3	7/8
				1	1
				3	1 1/16
3	ECO-107	8.50	11.75	4	1 1/8
				3	1 3/4
3 1/2	ECO-108	8.50	12.25	4	1 1/8
				3	1 3/4
4	ECO-109	8.75	12.50	4	1 1/8
				3	1 3/4

*Zinc Die Cast



Type ECO-100



Type ECS

Use:

Set-screw type weather resistant aluminum entrance caps for unthreaded rigid conduit or IMC service masts.

Material/Finish:

Aluminum/Natural


Third Party Certification:

 UL Listed: E-163167

Applicable Third Party Standards:

UL Standard: 514B
NEMA: FB-1

Trade Size (inches)	Catalog Number	Dimensions in Inches		No. Holes	Size Holes
		A	B		
2	ECS-105	5.50	7.00	2	3/4
				3	1
				1	1 1/16
2 1/2	ECS-106	7.25	10.25	3	7/8
				1	1
				3	1 1/16
3	ECS-107	8.75	10.75	4	1 1/8
				3	1 3/4
3 1/2	ECS-108	9.25	13.50	4	1 1/8
				3	1 3/4
4	ECS-109	9.25	13.50	4	1 1/8
				3	3/4



Type ECS-105

