

073031208 -- Dusttight Grips



Insulated

Kellems Strain Relief Grips connect flexible cord or bus drop cable to electrical enclosures. For indoor use only, they are available with either insulated or non-insulated aluminum fittings, and feature single weave, galvanized steel mesh grips.

Product Specifications

Product Type	Dusttight Grips
Thread Type	N.P.T.
Dusttight Grip Insulated	Yes
Grip Style and Material	Straight Aluminum Connector Stainless Grip
Grip Cord Range (Diameter)	.43" - .54" (1.09 - 1.37)
Grip Thread Size	1/2"
Operating Temperature	-30°F to +225°F (-34°C to +107°C)
Mesh Grip Flammability Rating	UL 94-HB
Fitting Flammability Rating	UL 94-V2
Recommended Knockout Hole Size	.859 to .906 (2.18 - 2.30)
Hazardous Locations	Suitable for use in hazardous locations per Class I, Div. 2, Class II, Div. 1 & 2, Class III, Div. 1 & 2.
Mesh Length @ Nom. Dia.	4 3/4" (12.06)
Dimension A	1" (2.54)
Certifications	UL Listed CSA Certified
UPC Number	78358533008
Weight in LBs	0.05
Link to Drawing Library	Click here for Library
Link to PDF Catalog	Click here for Catalog

