

# MT789-HGW

# Lev-Lok® Modular Devices



UPC Code: 07847741238

Country of Origin: China

NEMA: 5-20R



## Brand Features

The Lev-Lok® Modular Wiring Device System is engineered for fast and easy installation. These devices employ a simple twist and lock wiring module that ensures a safe, reliable connection while at the same time providing for extremely fast and easy installation. Lev-Lok brand wiring devices address the reliability and performance concerns of specification engineers without sacrificing the contractor's need for fast, easy installation. Available in extra heavy duty hospital and industrial grades, and heavy duty commercial grade platforms.

## Item Description

20 Amp, 125 Volt, NEMA 5-20R, 2P, 3W, Lev-Lok®, SmartlockPro, Tamper-Resistant, GFCI Duplex Receptacle, Hospital Grade, No Feed-Thru, Modular Terminals, Steel Strap – WHITE

## Technical Information

### Electrical Specifications

**Dielectric Voltage Withstand:** 1500V minimum per UL 498

**Maximum Working Voltage:** 125V as rated

**Current Interrupting:** 2 kA

**AC Horsepower Ratings:** 1 HP for both receptacle and buttons

**Trip Level:** 5mA plus or minus 1mA

**Temperature Rise:** Max 30°C temp rise at full-rated current after 150 cycles of OL at 150% rated DC current

### Environmental Specifications

**Flammability:** Rated V-2 per UL94

**Operating Temperature:** -35degC to 65degC (-31degF to 149degF)

### Material Specifications

**Cover Material:** Nylon

**Base Material:** Polycarbonate

**Mounting Strap:** Multi-Piece Steel with Brass Ground Contacts

**Ground Clips:** Brass

**Line Contacts:** 0.031" thick Brass, Double Wipe

**Locking Pins:** Solid Brass

**Mounting Screws:** Triple Combination Head, Steel

**Standards and Certifications:** NEMA WD-1 & 6, ANSI C-73, UL 943 Class A(GFCI), UL 498(Receptacle), CSA C22.2 No. 42, NOM 057

### Mechanical Specifications

**Product ID:** Ratings are permanently marked on device

### Product Features

**Grounding:** GFCI Ground Fault

**Feature:** Lev-Lok Hospital Grade

**Amperage:** 20 Amp

**Voltage:** 125 Volt

**NEMA:** 5-20R

**Pole:** 2

**Wire:** 3

**Termination:** Modular Terminals

**Face Material:** Nylon

**Base Material:** Polycarbonate

**Mounting Strap:** Multi-Piece Steel

**Locking Pins:** Solid Brass

**Ground Clips:** Brass

**Color:** White

**Standards and Certifications:** UL/CSA/NOM

**Warranty:** 10 Year Limited

### Standards and Certifications

**NEMA:** WD-6

**UL498HG:** File E13399

**ANSI:** C-73

**CSA C22.2 No. 42:** File LR-57811

**NOM:** 057

