

Pass & Seymour



Slater® Plastic Boxes Switch & Outlet Boxes

With Captive Mounting Nails on Each End with Quick/Click®



S1-18-R



S2-35-R




S2-35-RACMH




S3-54-RAC



S4-68-RAC



S4-68-RAC



EXT1



EXT2

Catalog Number	Cu. In. Vol.	Description	Dimensions (inches)			Wire Fill (AWG)	Qty. Per Carton
			L	W	D		
Switch & Outlet Boxes with Quick/Click®							
S1-18-R	18.0	Single gang. 2 Quick/Entries® each end.	3 ³ / ₄	2 ¹ / ₄	2 ²³ / ₃₂	9 No. 14 8 No. 12 7 No. 10	100
S2-35-RAC	35.0	Two gang. 4 Auto/Clamps® each end.	3 ³¹ / ₃₂	3 ³¹ / ₃₂	3 ³ / ₈	17 No. 14 15 No. 12 14 No. 10	50
S2-35-RACMH	35.0	Two gang. 4 Auto/Clamps each end. 3" depth for manufactured housing walls.	3 ³ / ₄	4 ¹ / ₁₆	3	17 No. 14 15 No. 12 14 No. 10	100
S3-54-RAC	54.0	Three gang. 6 Auto/Clamps each end.	3 ³¹ / ₃₂	5 ²⁵ / ₃₂	3	27 No. 14 24 No. 12 21 No. 10	50
S4-68-RAC*	68.0	Four gang. Rear stabilizing bar virtually eliminates inward movement. 6 Auto/Clamps each end.	3 ¹³ / ₁₆	7 ¹³ / ₁₆	3	34 No. 14 30 No. 12 27 No. 10	25
Deep Switch & Outlet Boxes with Quick/Click							
S1-22-R	22.5	Single gang deep. 2 Quick/Entries each end. Extra deep for dimmers, GFCIs and thermostats, yet suitable for 2 x 4 construction.	3 ³ / ₄	2 ¹ / ₄	3 ³ / ₈	11 No. 14 10 No. 12 9 No. 10	100

All boxes are UL Listed.

UL Classified for 2 Hour Fire Resistance (*Does not apply to Catalog Number S4-68-RAC).

Catalog Number	Cu. In. Vol.	Description	Qty. Per Carton
Wall Box Extension Rings			
EXT1	1.0	Single gang. 1/4" thick. Stackable.	10
EXT2	1.0	Two gang. 1/4" thick. Stackable.	10