



Explosionproof fixture for ceiling mounting. Cast aluminum housing, heat and impact resistant globe. Fits all incandescent lamps up to 300 Watt PS-25. Lamp not supplied.

Color: N/A

Weight: 11.9 lbs

<b>Project:</b>	<b>Type:</b>
<b>Prepared By:</b>	<b>Date:</b>

Lamp Info		Ballast Info	
Type:	PS-25	Type:	N/A
Watts:	300W	120V:	N/A
Shape/Size:	N/A	208V:	N/A
Base:	N/A	240V:	N/A
ANSI:	N/A	277V:	N/A
Hours:	N/A	Input Watts:	0W
Lamp Lumens:	N/A		
Efficacy:	N/A		

**Technical Specifications**

**Listings**

**UL Listing:**

Suitable for wet locations.

**Construction**

**Housings:**

Heavy cast aluminum. Unit withstands 1490 lbs. per square inch hydrostatic pressure.

**Globe:**

Impact and heat resistant clear prismatic design affords excellent light control.

**Finish:**

Formulated for high-durability and long lasting color.

**Reflectors:**

Heavy gauge aluminum with highly reflective white acrylic finish.

**Hub Size:**

3/4".

**Hub Count:**

4

**Weight:**

12 lb / 5.4 kg.

**Electrical**

**Wiring:**

Wiring is factory sealed. Inspection hole provides easy access to splice compartment.

**Socket:**

Medium base glazed porcelain. Leads pass through sealing compound that separates lamp chamber from wiring compartment. Heavy gauge nickel plated copper components. Spring loaded center contact.

**Other**


**Refer to the catalog for Class and Division specifications:**

**Guard supplied:**

**Buy American Act Compliance:**

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

## Dimensions



## Features

- Fixture comes complete with built-in junction box
- Cast aluminum construction with gray polyester powder coat finish
- Easy relamping with a single thumb screw
- Factory sealed for easy installation
- Heat and impact resistant prismatic glass globe
- Die cast guard
- Easy field installation