



Application


- For use on threaded Rigid/IMC conduit to provide a smoothly rounded surface at the entrance of raceways

Product Features

- Insuliner temperature rated at 150° C
- Malleable construction insures mechanical protection for the raceway
- Zinc electro plated for corrosion protection

Compliances

-  – Standard 514B
-  – C22.2 #18



A = O.D.
B = Thickness
C = I.D.



Insulated Bushings
Malleable Iron

ORDERING INFORMATION - DIMENSIONS

INSULATED BUSHINGS - MALLEABLE IRON

CATALOG NUMBER	TRADE SIZE	UNIT CTN. QTY.	SHIP CTN. QTY.	UPC BAR CODE
1132	1/2"	—	100	—
1133	3/4"	—	50	—
1134	1"	—	25	—
1135	1-1/4"	—	25	—
1136	1-1/2"	—	25	—
1138	2"	—	10	—
1126	2-1/2"	—	10	—
1127	3"	—	5	—
1128	3-1/2"	—	5	—
1129	4"	—	5	—

DIMENSIONS

CATALOG NUMBER	A	B	C THROAT DIA.
1132	1-5/32"	9/16"	37/64"
1133	1-13/32"	9/16"	49/64"
1134	1-3/4"	21/32"	31/32"
1135	2-1/8"	21/32"	1-9/32"
1136	2-11/32"	23/32"	1-1/2"
1138	2-23/32"	23/32"	1-61/64"
1126	3-9/32"	15/16"	2-19/64"
1127	3-7/8"	15/16"	2-29/32"
1128	4-13/32"	15/16"	3-3/8"
1129	4-29/32"	15/16"	3-55/64"