

We maintain only the highest standards in the materials, production techniques and quality control measures used to manufacture our fasteners, assuring consistent, optimum quality in every fastener.


FASTENER TERMINOLOGY SUFFIX

K = Knurled X = Collated C = 100 count
 B = Black SD = Washer M = 1000 count
 E = Ramguard TH = Top Hat

SELECTION CHART

BLACK TRACK PINS

Designed for use in concrete and structural steel applications. Available in 100-pack or 1000-pack per box.




PART NUMBER	SHANK LENGTH		721/ R25	ROCKET	D60/ D45A	SA270	XT540	COBRA	MASTERSHOT/ RS22
	IN.	(MM)							
1506B	3/4	(19.1)	•	•	•	•	•	•	•

Shank diameter = .145 Head diameter = .300

PLATED PINS

Designed for use in concrete and structural steel applications. 100 per box.




PART NUMBER	SHANK LENGTH		721/ R25	ROCKET	D60/ D45A	SA270	XT540	COBRA	MASTERSHOT/ RS22
	IN.	(MM)							
1503K	1/2 Knurled	(12.7)	•	•	•	•	•	•	•
1506	3/4	(19.1)	•	•	•	•	•	•	•
1508	1	(25.4)	•	•	•	•	•	•	•
1510	1-1/4	(31.8)	•	•	•	•	•	•	•
1512	1-1/2	(38.1)	•	•	•	•	•	•	•
1514	2	(50.8)		•	•	•	•	•	•
1516	2-1/2	(63.5)				•	•	•	•
1524	3	(76.2)				•	•		•

Shank diameter = .145 Head diameter = .300

WASHERED PINS

Washer increases bearing surface against the material to be fastened. 100 per box. 16 gage metal washer. 7/8" diameter washer after 16 gage.




PART NUMBER	SHANK LENGTH		721/ R25	ROCKET	D60/ D45A	SA270	XT540	COBRA	MASTERSHOT/ RS22
	IN.	(MM)							
1506SD	3/4	(19.1)	•	•	•	•	•	•	•
1508SD	1	(25.4)	•	•	•	•	•	•	•
1510SD	1-1/4	(31.8)	•	•	•	•	•	•	•
1512SD	1-1/2	(38.1)	•	•	•	•	•	•	•
1514SD	2	(50.8)	•	•	•	•	•	•	•
1516SDC	2-1/2	(63.5)		•	•	•	•	•	•
1524SDP*	3	(76.2)				•	•	•	•

*Square washer indicates 3" pin has been installed Shank diameter = .145 Head diameter = .300

RAMGUARD PINS

Coated to improve corrosion resistance in treated lumber and other applications. 100 per box. Recommended for threaded lumber applications.



PART NUMBER	SHANK LENGTH		721/ R25	D60/D45A	ROCKET/ SA270	XT540	COBRA	MASTERSHOT/ RS22
	IN.	(MM)						
1516SDE	2-1/2	(63.5)			•	•	•	•
1524SDE*	3	(76.2)		•	•	•	•	•

Shank diameter = .145 (SP178E = .150/.180)
 Head diameter = .300 *Square washer indicates 3" pin has been installed

* 1500 Series Coated with RamGuard
 * SP Series Coated with Triple Zinc