

We maintain only the highest standards in the materials, production techniques and quality control measures used to manufacture our fasteners, assuring consistent, optimum quality in every fastener.

### FASTENER TERMINOLOGY SUFFIX

K = Knurled                      X = Collated                      C = 100 count  
 B = Black                        SD = Washer                      M = 1000 count  
 E = Ramguard                    TH = Top Hat


### ADVANTAGES

ITW Ramset powder actuated fasteners are specifically fabricated to meet the exacting requirements of toughness and durability that enable them to penetrate dense concrete and structural quality steel. All Ramset fasteners with .300 head will fit into tools with 8mm barrels.

### SELECTION CHART

#### BLACK TRACK PINS


Designed for use in concrete and structural steel applications. Available in 100-pack or 1000-pack per box.

	PART NUMBER	SHANK LENGTH		R25	SA270	XT540	COBRA	MASTER CARTON QTY
		IN.	(MM)					
	1506B	3/4	(19.1)	•	•	•	•	5000

Shank diameter = .145      Head diameter = .300

#### PLATED PINS


Designed for use in concrete and structural steel applications. 100 per box.

	PART NUMBER	SHANK LENGTH		R25	SA270	XT540	COBRA	MASTER CARTON QTY
		IN.	(MM)					
	1503K	1/2 Knurled	(12.7)	•	•	•	•	5000
	1506	3/4	(19.1)	•	•	•	•	5000
	1508	1	(25.4)	•	•	•	•	5000
	1510	1-1/4	(31.8)	•	•	•	•	1000
	1512	1-1/2	(38.1)	•	•	•	•	1000
	1514	2	(50.8)	•	•	•	•	800
	1516	2-1/2	(63.5)	•	•	•	•	800
	1524	3	(76.2)	•	•	•	•	600

Shank diameter = .145      Head diameter = .300

#### WASHERED PINS


Washer increases bearing surface against the material to be fastened. 100 per box. 16 gage metal washer. 7/8" diameter washer.

	PART NUMBER	SHANK LENGTH		R25	SA270	XT540	COBRA	MASTER CARTON QTY
		IN.	(MM)					
	1506SD	3/4	(19.1)	•	•	•	•	1000
	1508SD	1	(25.4)	•	•	•	•	1000
	1510SD	1-1/4	(31.8)	•	•	•	•	1000
	1512SD	1-1/2	(38.1)	•	•	•	•	1000
	1514SD	2	(50.8)	•	•	•	•	1000
	1516SDC	2-1/2	(63.5)	•	•	•	•	600
	1524SDP*	3	(76.2)	•	•	•	•	600

\*Square washer indicates 3" pin has been installed      Shank diameter = .145      Head diameter = .300

#### RAMGUARD PINS

Coated to improve corrosion resistance in treated lumber and other applications. 100 per box. Recommended for treated lumber applications.

	PART NUMBER	SHANK LENGTH		R25	SA270	XT540	COBRA	MASTER CARTON QTY
		IN.	(MM)					
	1516E	2-1/2	(63.5)	•	•	•	•	800
	1516SDE	2-1/2	(63.5)	•	•	•	•	600
	1524SDE*	3	(76.2)	•	•	•	•	600

Shank diameter = .145      \*Square washer indicates 3" pin has been installed      \*1500 Series Coated with RamGuard      Head diameter = .300