

# Rittal – The System.

Faster – better – everywhere.

## Door-operated switch – SZ 4127.010

Date : Jul 1, 2015

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# Door-operated switch – SZ 4127.010

erstellt am : 01.07.2015 build on www.rittal.com/th-en



## Product description

**Packs of:** 1 pc(s).

**EAN:** 4028177497740

**Customs tariff number:** 85369085

**eCl@ss 5.1:** 27189241

**eCl@ss 7.0:** 27119116

## Product features

**Design:** Without connection cable

**Rated operating voltage:** 400 V

**Technical specifications:**  
240 V AC, 6 A  
125 V AC, 8 A  
24 V AC, 6 A  
24 V DC, 6 A



**Rated insulation voltage:** 400 V AC

**Rated impulse withstand voltage, phase to phase:** 6000 V AC


**Weight/PU:** 0.08 kg

## Approvals

Approvals:


 [CSA \(EN\)](#)  
 [UL \(DE\)](#)

Declarations:

 [Declaration of conformity \(DE\)](#)

## Downloads

Documentation:

 [Info sheet \(PT, ZH, CS, FR, JP, RU, ES, DE, FI, KO, SV, NO, NL, VI, EN, HU, PL, IT, DA\)](#)

CAD drawings:

[Request](#)