

# UNIVERSAL SWITCH STICKS

One, two and three section hotsticks have a standard splined universal head. 1.25" dia. switch sticks are supplied with a #9971 Prong. A Heavy Duty Disconnect Prong #9969 is supplied on all others.



9969 Prong



9971 Prong



Universal Switch Stick

CAT. NO.	DIMENSIONS: DIA. X LENGTH		WEIGHT EA. lbs. (kgs)
	in x ft.	mm x m	
<b>ONE SECTION</b>			
4213	1.25 x 4	31.7 x 1.2	2.6 (1.2)
4214	1.25 x 6	31.7 x 1.8	3.4 (1.5)
4215	1.25 x 8	31.7 x 2.4	4.1 (1.9)
4216	1.25 x 10	31.7 x 3	4.9 (2.2)
4217	1.25 x 12	31.7 x 3.6	5.6 (2.5)
4218	1.25 x 14	31.7 x 4.3	6.4 (2.9)
4219	1.5 x 8	38.1 x 2.4	5.4 (2.5)
4220	1.5 x 10	38.1 x 3	6.5 (3)
4221	1.5 x 12	38.1 x 3.6	7.5 (3.4)
4222	1.5 x 14	38.1 x 4.3	8.6 (3.9)
4223	1.5 x 16	38.1 x 4.9	9.8 (4.3)
4225	1.5 x 20	38.1 x 6	11.7 (5.3)

	OAL Length		Top		Bottom		Weight	
	ft.	m	in. x ft.	mm x m	in. x ft.	mm x m	lbs.	(kgs)
4036	8	2.4	1.25 x 4	31.7 x 1.2	1.25 x 4	31.7 x 1.2	4.2	(1.9)
4037	10	3	1.25 x 5	31.7 x 1.5	1.25 x 5	31.7 x 1.5	5.2	(2.2)
4038	12	3.6	1.25 x 6	31.7 x 1.8	1.5 x 6	38.1 x 1.8	6.9	(3.1)
4039	14	4.3	1.25 x 6	31.7 x 1.8	1.5 x 8	38.1 x 2.4	7.9	(3.1)
4040	16	4.9	1.25 x 8	31.7 x 2.4	1.5 x 8	38.1 x 2.4	8.6	(3.9)
4041	18	5.5	1.25 x 8	31.7 x 2.4	1.5 x 10	38.1 x 3	9.6	(4.4)
4042	20	6	1.25 x 10	31.7 x 3	1.5 x 10	38.1 x 3	10.4	(4.7)

	OAL Length		Top		Bottom		Weight	
	ft.	m	in. x ft.	mm x m	in. x ft.	mm x m	lbs.	(kgs)
4043	12	3.6	1.25 x 4	31.7 x 1.2	1.5 x 4	38.1 x 1.2	7.7	(3.5)
4044	15	4.6	1.25 x 5	31.7 x 1.5	1.5 x 5	38.1 x 1.5	9.1	(4.1)
4045	18	5.5	1.25 x 6	31.7 x 1.8	1.5 x 6	38.1 x 1.8	10.5	(4.7)
4046	20	6	1.25 x 8	31.7 x 2.4	1.5 x 6	38.1 x 1.8	16.5	(7.5)

<b>HEAD ONLY</b>								
9840			1.25	31.7		Universal Head	0.2	(0.1)
9841			1.5	38.1		Universal Head	0.3	(0.1)



FRP Splices with Button