

Malleable Iron Straight Liquidtight Connectors

With Aluminum Lugs For Liquidtight Flexible Metallic Conduit

Application:

Connects conduit and terminates bonding conductor run externally across liquidtight conduit.

Features:

- Tapered threaded male hub NPT
- Compact, slim diameter with small turning radius
- Furnished with Insulated throat, steel locknut, and sealing ring
- Liquidtight/Raintight/Oiltight
- Suitable for grounding & wet locations
- Long ferrule prevents pullout and tight bend conduit 'pop-out'
- UL Listed liquidtight flexible metal conduit fittings are suitable for use in the following Hazardous Locations under NEC 501-4(b), 502-4(a)(2); Class I, Div.2; Class II, Div. 1 and 2; and Class III, Div. 1 and 2 and are suitable for grounding in sizes 3/8" through 1-1/2" under NEC 351-1


Standard Materials:

Malleable Iron/
Steel Ferrule/
Aluminum Grounding Lug

Standard Finish:

Zinc Plated

 **UL Listed:**
E212551



All Furnished with Insulated Throats

CATALOG NUMBER	TRADE SIZE	LUG SIZE	DIM A	DIM B	DIM C	DIM D	UNIT PACK	STD. PACK	WEIGHT (LBS.) PER 100	NAED MFG #78-5994 UPC/DCI #
SLT47ALT	3/8"	#4-#14	1.14	0.50	1.15	0.75	25	250	18	50000
SLT27ALT	1/2"	#4-#14	1.25	0.50	1.28	0.75	25	250	20	50001
SLT28ALT	3/4"	#4-#14	1.28	0.52	1.55	0.75	10	100	31	50002
SLT29ALT	1"	#4-#14	1.43	0.65	1.80	0.75	5	50	42	50003
SLT30ALT	1-1/4"	#4-#14	1.50	0.66	2.25	0.75	5	50	57	50004
SLT31ALT	1-1/2"	#4-#14	1.61	0.73	2.44	0.75	10	50	73	50005
SLT32ALT	2"	#4-#14	1.76	0.75	2.97	0.75	5	25	101	50006
SLT33ALT	2-1/2"	#1/0-#8	2.18	1.01	4.01	1.13	1	10	373	50007
SLT34ALT	3"	#1/0-#8	2.50	1.15	4.18	1.13	1	10	465	50008
SLT60ALT	3-1/2"	#3/0-#6	2.61	1.18	5.25	1.50	1	10	686	50009
SLT61ALT	4"	#3/0-#6	2.74	1.25	5.78	1.50	1	5	807	50010
SLT62ALT	5"	#6-#250MCM	3.13	1.50	6.06	1.69	-	1	1058	50011
SLT63ALT	6"	#6-#250MCM	3.13	1.56	7.50	1.69	-	1	1395	50012

Also available with copper lugs. See page 88.

