


• Revised •
01/22/13



Meter Centers

EUSERC Compliant Side-by-Side Meter-Main Breaker, 1-Phase, 3-Wire 120/240V AC

- UL listed
- Designed to meet EUSERC standards
- Underground Feed Applications (some with OH provisions)
- Load wiring may exit top or bottom
- 22,000 AIC Rated
- Pad locking provisions on all devices
- Surface and semi-flush units available
- Side hinge door removable by backing out only one screw
- Suitable for use only as service entrance equipment
- Contact local utility to confirm meter socket approval prior to installation
- See end of section for dimensions and wiring diagrams



EUSERC Compliant Meter-Main Breaker, Factory and Field Options listed, 125-200amp^{③④}

Old Cat Number	New Cat Number	Utility Incoming	By-pass Type	No. of Spaces	No. of Circuits	Dimensions			Main Breaker	Short Circuit Rating	Mounting	Hub Provisions	5th Jaw	Cover Type
						H	W	D						
MM0406L1125FEC	MM0202L1125EFC ^{①②}	OH/UG	none	2	2	23.6	14.5	5	—	22,000	Flush	RX (top) / HC (bot)	EMC5J	Ring
MM0406L1125SEC	MM0202L1125ESC ^①										Surface			
MM0406L1200FEC	MM0202L1200EFC ^①	OH/UG	none	2	2	28.6	14.5	7	—	22,000	Flush	RX (top) / HC (bot)	EMC5J	Ring
MM0406L1200SEC	MM0202L1200ESC ^①							5			Surface			
N/A	MM0202B1100ESC	OH/UG	none	2	2	23.6	14.5	5	Q2100H	22,000	Surface	RX (top) / HC (bot)	EMC5J	Ring
N/A	MM0202B1200ESC								QN2200H					

Catalog Number	Amp Rating (Cont.)	Utility Incoming	Bypass Type	No. of Spaces	No. of Circuits	Dimensions (inches)			Main Breaker	Short Circuit Rating	Mounting	Hub Provision	5th Jaw	Cover Type
						H	W	D						

EUSERC Compliant Meter-Main Breaker, Field Installed Main Main Breakers, 400amp max.^①

MM0404L1400SC	320	OH/UG	None	4	2	39.7	33.2	6.4	(2) Field QP(H), QNR(H)	22,000	Surface	HD (top) / HC (bot)	—	Ring
MM0404L1400FD		UG		4	2	39.7	30.2	7.4			Flush	None (top) / HC (bot)	—	

EUSERC Compliant Meter-Main Breaker, with Test Block Bypass & Field Installed Main Main Breakers, 400amp max.^①

MM0404L1400SCS	320	OH/UG	Test Block	4	2	39.7	33.2	6.4	(2) Field QP(H), QNR(H)	22,000	Surface	HD (top) / HC (bot)	—	Ring
MM0404L1400FDS		UG		4	2	39.7	30.2	7.4			Flush	None (top) / HC (bot)	—	

① Main breaker not included.
 ② Flush adjustable for 2x4 walls only.

③ Dimensional and other technical data is applicable for "New Catalog Numbers" ONLY.
 ④ UL Listed for Siemens and Murray breakers.