









A-51® Incandescent Factory Sealed Luminaire Accessories

For Group C and D Locations. Explosionproof

Suitable for use in Wet Locations. UNILETS for use with Threaded Metal Conduit.

Class I, Division 1 and 2, Groups C, D
Class II, Division 1 and 2, Groups E, F, G
Class III

Mounting Hoods		
Type	Hub Size (Inches)	Catalog Number
Pendant — One Hub, Rigid or Flexible Mounting		
	1/2	AAP-50
	3/4	AAP-75
	1	AAP-100
Ceiling — Four Hubs, Three Close-up Plugs		
	1/2	AAC-50
	3/4	AAC-75
	1	AAC-100
25° Stanchion — Not UL Listed — One Hub		
	1-1/2	AAN-150 ①
Long Bracket — Four Hubs, Three Close-up Plugs		
	1/2	AALB-50
	3/4	AALB-75
	1	AALB-100
15° Short Bracket — Two Hubs, One Close-up Plug		
	1/2	AASB-50
	3/4	AASB-75
Type	Catalog Number	
Fixture Units		
	60-100 W A-21	AAU-1N
	150-300 W A-23 & PS-25	AAU-15N
	200-300 W PS-30	AAU-2NS
Prismatic Glass Globes		
	60-100 W (AAU-1N)	AAGL-1PR
	150-300 W (AAU-15N)	AAGL-1PR
	200-300 W (AAU-2NS)	AAGL-2PR
Aluminum Guards		
	60-100 W (AAU-1N)	AAGU-1
	150-300 W (AAU-15N)	AAGU-1
	200-300 W (AAU-2NS)	AAGU-2

① 1-1/2" tapped hub furnished with a 1-1/2" to 1-1/4" reducer.




A-51® Incandescent Factory Sealed Luminaires

For Group A and B Locations. Explosionproof

Suitable for use in Wet Locations. UNILETS for use with Threaded Metal Conduit.

Class I, Division 1 and 2, Groups A, B, C, D
 Class II, Division 1 and 2, Groups E, F, G
 Class III

Mounting Hoods

	Type	Hub Size (Inches)	Catalog Number
Pendant		One Hub, Rigid or Flexible Mounting	1/2 AAP-50 ① 3/4 AAP-75 ①
Ceiling		Four Hubs, Three Close-up Plugs	1/2 AAC-50 3/4 AAC-75
15° Short Bracket		Two Hubs, One Close-up Plug	1/2 AASB-50 3/4 AASB-75

	Description	Catalog Number
Fixture Units	60-200 W	AAUA-15
	PS-25	
	200-300 W	AAUA-2
	PS-30	
Globe and Ring Assembly	60-200 W (AAUA-15)	AAGLA-15
	200-300 W (AAUA-2)	AAGLA-2
Aluminum Guards	60-200 W (AAUA-15)	AAGUA-15
	200-300 W (AAUA-2)	AAGU-2
Medium Base Lamp Socket	60-200 W (AAUA-15)	AASPA-15
	200-300 W (AAUA-2)	AASPA-22
Connection Block	Fits all A-51 and AA-51 mounting hoods 60-300 W	VPT-7

① Group A pendant mount only.

LIGHTING: EXPLOSIONPROOF – AREA – INCANDESCENT

