



DCB1800B 1800 WATT PORTABLE POWER STATION AND PARALLEL BATTERY CHARGER



The 1800 Watt Portable Power Station™ and Parallel Battery Charger allows for AC power in remote locations for convenient portable power. Able to run most corded tools, it provides 1800 Watts (15 amps) continuous power and 3600 Watts peak power. The DCB1800B runs on four DEWALT 20V MAX* batteries (including FLEXVOLT), and for high power applications, four 20V MAX* 3.0Ah DEWALT Batteries (DCB200) or higher amp hour are recommended to provide the best results. Not only can the 1800 Watt Portable Power Station™ power a corded tool remotely, but it also becomes a multi-port parallel charger for up to four DEWALT 20V MAX* Batteries (including FLEXVOLT) when plugged into a wall outlet via extension cord (batteries and extension cord sold separately). Compact and lightweight, the 1800 Watt Portable Power Station™ weighs just 18lbs (without batteries) and is easily portable. Without the need for gas to run, there are no fumes or carbon monoxide emitted from the device. In addition, the 1800 Watt Portable Power Station™ can be used to provide temporary power in areas where noise is restricted such as a jobsite with strict regulations. With an integrated temperature-controlled cooling fan and heavy-duty roll cage, the Portable Power Station™ is a durable and convenient power solution for a variety of uses.

FEATURES & SPECS

FEATURES & SPECS

FEATURES

- 1800 Watt Portable Power Station
- Four 20V MAX* batteries in (including FLEXVOLT), 15 amps out
- 4 Port Parallel Charger
- Batteries and extension cord sold separately

SPECIFICATIONS

120V RECEPTACLES	1
CHARGING CONNECTION	MALE 120V PLUG
CHARGING TIME	2 HOURS, 4.0 AH BATTERY
HEIGHT	10.75 IN
LENGTH	12.75 IN
MAX CURRENT (120V/240V)	30 AMPS
RATED AC OUTPUT	1800 WATTS
REQUIRED NUMBER OF BATTERIES	4
SHIPPING WEIGHT	22 LBS
TEMPERATURE RANGE	32-104 F °
WIDTH	21.3 IN

BATTERIES COMPATIBLE	20V MAX*
CHARGING RATE	2.0 AMPS
COMPATIBLE WITH	20V MAX* BATTERIES
INDICATOR LIGHTS	INVERTER AND CHARGER, OPERATION AND FAULT, LOW BATTERY
MAX AC OUTPUT	3600 WATTS
QUANTITY OF BATTERIES CHARGED	4
RATED CURRENT (120V/240V)	15 AMPS
SEQUENTIAL OR PARALLEL CHARGING	PARALLEL
SINEWAVE TYPE	MODIFIED
WEIGHT WITHOUT BATTERIES	18 LBS

INCLUDES

- unit