

T5 Miniature Bipin (5/8" diameter)

T8 Medium Bipin (1" diameter)

PREHEAT FLUORESCENT LAMPS

Miniature T5 Preheat Lamps (Starter Required)

Nominal Wattage	Bulb Shape	Nom. Length (in)	MDL (in)	Base	Product Number	Ordering Abbreviation	Pkg Qty	Average Rated Life @3hrs/start (hrs)	CCT (K)	CRI	Initial Lumens at 25°C/77°F	Notes
4	T5	6	5.91	Mini Bipin	21364	F4T5/CW	25	6000	4200	60	135	☞,12,13,17
6	T5	9	8.91	Mini Bipin	21365	F6T5/CW 25/CS	25	7500	4200	60	270	☞,12,13,17
8	T5	12	11.91	Mini Bipin	20819	F8T5/SW/BL/1/6	6	7500	3000	52	400	☞,12,13,17
					21367	F8T5/WW 25/CS	25	7500	3000	52	400	☞,12,13,17
					21361	F8T5/CWX 25/CS	25	7500	4100	87	270	☞,12,13,17
					21366	F8T5/CW 25/CS	25	7500	4200	60	390	☞,12,13,17
13	T5	21	20.91	Mini Bipin	21369	F13T5/WW 25/CS	25	7500	3000	52	880	☞,12,13,17
					21368	F13T5/CW	25	7500	4200	60	860	☞,12,13,17
					21315	F13T5CW/BL/1/6	6	7500	4200	60	860	☞,12,13,17
18	T5	30	29.91	Mini Bipin	20911	F18T5/WW/RS/SMBASE	24	7500	3000	52	1325	☞,12,13,17
					20909	F18T5/CW/RS	24	6000	4200	62	1325	☞,12,13,17

Standard T8 Preheat Lamps (Starter Required)

Nominal Wattage	Bulb Shape	Nom. Length (in)	MDL (in)	Base	Product Number	Ordering Abbreviation	Pkg Qty	Average Rated Life @3hrs/start (hrs)	CCT (K)	CRI	Lumens Initial (Mean) at 25°C/77°F	Notes
13	T8	12	11.71	Medium Bipin	21766	F13T8/CW	24	7500	4200	62	530 (460)	☞,12,13,17
14	T8	15	14.78	Medium Bipin	21486	F14T8/CW	24	7500	4200	60	685 (645)	☞,12,13,17
					21488	F14T8/D	24	7500	6500	76	575 (560)	☞,12,13,17
15	T8	18	17.78	Medium Bipin	21610	F15T8/D830	24	7500	3000	82	920 (845)	☞,12,13,17
					21701	F15T8/WW	24	7500	3000	52	845 (735)	☞,12,13,17
					21609	F15T8/D35	24	7500	3500	70	940 (845)	☞,12,13,17
					21616	F15T8/CW	24	7500	4200	60	825 (720)	☞,12,13,17
					21600	F15T8/D	24	7500	6500	76	700 (655)	☞,12,13,17
18	T8	24	23.78	Medium Bipin	23014	F18T8CW/K24	24	7500	4200	60	1190 (1035)	☞,12,13,17
					23027	F18T8CW/K26	24	7500	4200	60	1280 (1080)	☞,12,13,17
					23028	F18T8CW/K28	24	7500	4200	60	1360 (1130)	☞,12,13,17
					23030	F18T8CW/K30	24	7500	4200	60	1400 (1200)	☞,12,13,17

FLUORESCENT

Specifications subject to change without notice.