

The Hot One

Shop-tough and garage worthy

- Six-foot cord and heavy-duty bracket
- High/Low switch provides wattage choices
- 240 volt receptacle required

dimensions: 15-3/4"W x 17-1/2"H x 8-1/4"D



part	model	description	required receptacle	watts hi/low	volts	amps hi/low	btus hi/low	wt.lbs
10288	RCP402S	corded portable garage heater, red	NEMA 6-20R	4000/2667 3000/2000	240 208	16.7/11.1 14.4/9.6	13650/9100 10235/6825	29.8
10289	RCP502S	"	NEMA 6-30R	5000/3333 3750/2500	240 208	20.8/13.9 18.0/12.0	17060/11375 12795/8530	29.8

ELECTRONIC PROGRAMMABLE WALL THERMOSTATS



TH106



TH115

part	model	description	volts	amps
08160	TH106	electronic programmable single pole	120/208/240	16.7
08175	TH115-A-240D-B	electronic programmable double pole, retail pack	240/208	15
08165	TH115-A-240D-B	electronic programmable double pole	240/208	15

ELECTRONIC NON-PROGRAMMABLE WALL THERMOSTATS



TH401



TH114

part	model	description	volts	amps
72838	TH401	electronic non-programmable single pole	120/208/240	10.4
08172	TH114-A-240D-B	electronic non-programmable double pole, retail pack	240/208	15
08162	TH114-A-240D-B	electronic non-programmable double pole	240/208	15
08152	TH114-A-120-S	electronic non-programmable single pole	120	16.7

MECHANICAL WALL THERMOSTATS



T521/
T522



T410
White



T410
Almond



T410
Taupe



white part	almond part	taupe part	model	description	volts	amps
08121			T410A	non-programmable single pole, 40°F to 80°F, retail pack	120/208/240	22
08122			T410B	non-programmable double pole, 40°F to 80°F, retail pack	120/208/240	22
72801	72830	72821	T410A	non-programmable single pole, 40°F to 80°F	120/208/240	22
72802	72831	72822	T410B	non-programmable double pole, 40°F to 80°F	120/208/240	22
72865			T521-W	non-programmable single pole, 41°F to 95°F	120/208/240	22
72866			T522-W	non-programmable double pole, 41°F to 95°F	120/208/240	22

ELECTRIC BASEBOARD ACCESSORIES

*Add suffix W or A to model to designate color



SBFT2



BTF2



LTF240



BRF12



BLF

white part	almond part	*model	description	volts	amps
03400	n/a	SBFT2	Smart-Base built-in thermostat kit, electronic programmable, double pole, 40°F to 85°F, retail pack	240/208	12.6
08734	03365	BTF2	built-in thermostat kit, double pole, retail pack, 40°F to 85°F	120/208/240	22
14925	14920	BTF2	built-in thermostat kit, double pole, 40°F to 85°F	120/208/240	22
08732	03366	BTF1	built-in thermostat kit, single pole, retail pack, 40°F to 85°F	120/208/240	22
14915	14910	BTF1	built-in thermostat kit, single pole, 40°F to 85°F	120/208/240	22
14963	14960	LTF240	built-in load transfer switch receptacle kit	240	
14902	14900	BRF12	built-in receptacle requires separate supply wire	120	
14932	14930	BTF1TP	built-in thermostat kit, single pole, tamper proof, 40°F to 85°F	120/208/240	22
14942	14940	BTF2TP	built-in thermostat kit, double pole, tamper proof, 40°F to 85°F	120/208/240	22
14971	14970	BLF1	built-in corner connector, inside 90°		