



Log in | Register

search



Switch to

Products ▼ Market ▼ Solutions ▼ Resources ▼ About Us ▼

Start --> Search=TN108F* --> TN10-8F



TN10-8F

Copper Terminal, Fork Tongue, 12-10 AWG, #6-#8 Stud, Nylon Insulated, Funnel Entry, Tin Plated, 600 Volts Max.

[Image](#) | [Line Art](#) | [3D Model](#) | [Video](#) | [Customer Drawing](#)

- [Email Datasheet](#)
- [Print Datasheet](#)
- [Add to Favorites](#)

[Specifications](#) | [Documents](#)

Dimensional | **Electrical** | **General** | **Other** | **Physical** | **Approvals / Certifications** | **Conductor(s)** | **Other Features**

Dimensional	
Max Insulation Diameter	0.209
Length (in)	1.01
Tongue Type	Fork
Pad Width (in)	0.31
Strip Length	11/32
Electrical	
Max Voltage Rating	600
General	
Product Description	Copper Terminal, Fork Tongue, 12-10 AWG, #6-#8 Stud, Nylon Insulated, Funnel Entry, Tin Plated, 600 Volts Max.
Other	

Bulk Package	YAES10N56F
Physical	
Type of Plating	Tin
Connector Type	Terminal - Fork
Color Code	Yellow
Insulation Type	Nylon
Plated (Yes or No)	Y
Approvals / Certifications	
UL Listed	Y
CSA Certified	Y
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N
Industry Standards	UL486
Conductor(s)	
Copper Solid Size (Range)	N/A
Copper Stranded (Range)	12 AWG-10 AWG
Other Features	
UPC	7818107321444

© BURNDY® LLC 2011-2013 | [Distributors](#) | [Sales](#) | [Terms of Use](#) | [Site Map](#)

