

# HYDRONIC ELECTRIC BASEBOARD HEATER

- Permanent mount unit, offered in 28" to 96" lengths from 400 to 2000 watts.
- Heating elements are immersed in a heat transferring liquid enclosed by a copper tube casing with aluminum fins.
- Powder coated 12 ga. heavy duty extruded aluminum housing construction with junction boxes located on each end of the unit.
- An automatic thermal linear limit is used along the entire heated length of the unit
- Wire guard extends along the entire outlet area of the baseboard.
- Commercial Brown unit has in-built wireway cover running the entire length of the unit.
- Field installed accessories include in-built thermostat kits, optional relays and disconnect switch among others
- Available in White or Commercial Brown powder coated finish.
- Special colors available, consult factory.
- Suitable for high altitude applications
- 10 Year element warranty



STANDARD WHITE		COMMERCIAL BROWN		WATTS	BTU's.	VOLTS	AMPS	HEATER LENGTH (IN.)	WT. (LBS)	WHITE LIST	BROWN LIST
UPC 686334	MODEL	UPC 686334	MODEL								
111416	E3904-28	111645	E3904-28C	400	1360	120	3.3	28	16	309	328
111423	F3904-28	111652	F3904-28C	400	1360	208	1.92				
111430	H3904-28	111669	H3904-28C	400/300	1360/1024	240 / 208	1.6 / 1.4				
111447	G3904-28	111676	G3904-28C	400	1360	277	1.4				
111454	E3906-36	111683	E3906-36C	600	2048	120	5	36	22	353	376
111461	F3906-36	111690	F3906-36C	600	2048	208	2.9				
111478	H3906-36	111706	H3906-36C	600/450	2048/1536	240 / 208	2.5 / 2.2				
111485	G3906-36	111713	G3906-36C	600	2048	277	2.2				
111492	E3910-48	111720	E3910-48C	1000	3413	120	8.3	48	27	411	437
111508	F3910-48	111737	F3910-48C	1000	3413	208	4.8				
111515	H3910-48	111744	H3910-48C	1000/750	3413/2560	240 / 208	4.2 / 3.6				
111522	G3910-48	111751	G3910-48C	1000	3413	277	3.6				
111539	E3912-60	111768	E3912-60C	1250	4265	120	10.4	60	33	469	510
111546	F3912-60	111775	F3912-60C	1250	4265	208	6				
111553	H3912-60	111782	H3912-60C	1250/938	4265/3201	240 / 208	5.2 / 4.5				
111560	G3912-60	111799	G3912-60C	1250	4265	277	3.6				
111577	E3915-72	111805	E3915-72C	1500	5100	120	12.5	72	41	527	563
111584	F3915-72	111812	F3915-72C	1500	5100	208	7.2				
111591	H3915-72	111829	H3915-72C	1500/1125	5100/3825	240 / 208	6.3 / 5.4				
111607	G3915-72	111836	G3915-72C	1500	5100	277	5.4				
111614	F3920-96	111843	F3920-96C	2000	6826	208	9.6	96	58	625	673
111621	H3920-96	111850	H3920-96C	2000/1500	6826/5100	240 / 208	8.3 / 7.2				
111638	G3920-96	111867	G3920-96C	2000	6826	277	7.2				