

# Rigid Conduit Bodies with Cover and Gasket

## Threaded LR Type

### Features

- Threaded LR type with cover and gasket
- NPT tapered hubs
- Suitable for use in concrete
- Suitable for use in wet locations

### Applications


- Provides access to conductors for pulling, splicing and maintenance

### Standard Material

- Copper free aluminum die cast
- Cover - Stamped steel
- Gasket- Neoprene rubber

### Standard Finish

- Powder coat



| Catalog Number | UPC   | Size          | Wire Size   |           | Unit Carton | Ship Case | Weight/Case | Inches |       |       |
|----------------|-------|---------------|-------------|-----------|-------------|-----------|-------------|--------|-------|-------|
|                |       |               | Max. Number | Max. Size |             |           |             | A      | B     | C     |
| <b>LR1CG</b>   | 21241 | <b>1/2"</b>   | 1           | 6 AWG     | 10          | 100       | 36          | 4.295  | 1.370 | 2.030 |
| <b>LR2CG</b>   | 21251 | <b>3/4"</b>   | 2           | 6 AWG     | 10          | 50        | 28          | 5.090  | 1.625 | 2.330 |
| <b>LR3CG</b>   | 21261 | <b>1"</b>     | 3           | 6 AWG     | 5           | 25        | 17          | 5.915  | 1.900 | 2.650 |
| <b>LR4CG</b>   | 21271 | <b>1-1/4"</b> | 3           | 2 AWG     | 2           | 10        | 15          | 7.894  | 2.770 | 3.385 |
| <b>LR5CG</b>   | 21281 | <b>1-1/2"</b> | 3           | 2 AWG     | 2           | 10        | 18          | 7.894  | 2.770 | 3.385 |
| <b>LR6CG</b>   | 21291 | <b>2"</b>     | 3           | 2/O AWG   | 1           | 5         | 14          | 10.134 | 3.335 | 3.810 |
| <b>LR7CG</b>   | 21301 | <b>2-1/2"</b> | 3           | 4/O AWG   | ---         | 1         | 7           | 13.000 | 4.063 | 5.709 |
| <b>LR8CG</b>   | 21311 | <b>3"</b>     | 3           | 250 MCM   | ---         | 1         | 7           | 12.750 | 4.682 | 5.506 |
| <b>LR9CG</b>   | 21321 | <b>3-1/2"</b> | 3           | 350 MCM   | ---         | 1         | 10          | 15.500 | 5.452 | 6.171 |
| <b>LR10CG</b>  | 21331 | <b>4"</b>     | 4           | 350 MCM   | ---         | 1         | 10          | 15.500 | 5.452 | 6.171 |