






Rigid Nonmetallic Conduit – Schedule 80 Elbows

Schedule 80 Elbows Standard Radius

Available in plain end only for use with nonmetallic solvent weld fittings.

Item	Plain End Part No.	Belled End Part No.	Size	Plain End Std. Ctn. Qty.	Belled End Std. Ctn. Qty.
90° Elbow 	UB9AD	—	1/2"	50	—
	UB9AD-CAR	—	1/2"	25	—
	UB9AE	—	3/4"	25	—
	UB9AE-CAR	—	3/4"	15	—
	UB9AF	—	1"	25	—
	UB9AF-CAR	—	1"	10	—
	UB9AG	—	1 1/4"	20	—
	UB9AG-CAR	—	1 1/4"	5	—
	UB9AH	—	1 1/2"	25	—
	UB9AH-CAR	—	1 1/2"	5	—
	UB9AJ	—	2"	20	—
	UB9AJ-CAR	—	2"	5	—
	UB9AK-CAR	—	2 1/2"	10	—
	UB9AL-CAR	—	3"	5	—
	UB9AN	—	4"	1	—
	UB9AP	UB9APB	5"	4	1
UB9AR	—	6"	1	—	—
45° Elbow 	UB7AD	—	1/2"	50	—
	UB7AE-UPC	—	3/4"	25	—
	UB7AF-UPC	—	1"	20	—
	UB7AG	—	1 1/4"	20	—
	UB7AH	—	1 1/2"	20	—
	UB7AH-CAR	—	1 1/2"	5	—
	UB7AL-UPC	—	2"	20	—
	UB7AK	—	2 1/2"	20	—
	UB7AL	—	3"	1	—
	UB7AN	—	4"	1	—
UB7AP	UB7APB	5"	4	1	1
UB7AR	—	6"	1	—	—
30° Elbow 	UB6AD	—	1/2"	50	—
	UB6AE	—	3/4"	25	—
	UB6AF	—	1"	25	—
	UB6AG	—	1 1/4"	5	—
	UB6AH	—	1 1/2"	25	—
	UB6AJ	—	2"	20	—
	UB6AK	—	2 1/2"	1	—
	UB6AL	—	3"	1	—
	UB6AN	—	4"	1	—
	UB6AP	—	5"	1	—
UB6AR	—	6"	1	—	—
22 1/2° Elbow 	UB5AL	—	3"	5	—
	UB5AN	—	4"	1	—
11 1/4° Elbow 	UB3AL	—	3"	1	—
	UB3AR	—	6"	1	—

Flexible PVC Elbows






- UL Listed for exposed and direct burial applications in accordance with Article 356 of 2002 NEC
- 0° - 90° bending and offset applications
- O-ring seal for moisture tight connections
- Maintains round shape throughout bend
- Sunlight resistant
- Non-corrosive – all PVC and Neoprene material
- Fully assembled and ready to use

Part No.	Size	Std. Ctn. Qty.	Std. Ctn. Wt. (lbs.)	Length Fully Assembled
UAFAAD	1/2"	8	1.6	8.5"
UAFAE	3/4"	6	1.9	9.6"
UAFAF	1"	6	2.4	11.9"

Special Radius

ETL Listed to UL 651 in compliance to the NEC

UL LISTED E35297

Segment	Plain End Part No.	Belled End Part No.	Nom. Diam.	Radius (in.)	Plain End Std. Ctn. Qty.	Belled End Std. Ctn. Qty.		
90° Elbow 	UB9CF	—	1"	18"	1	—		
	UB9DF	—	1"	24"	1	—		
	UB9FF	—	1"	36"	1	—		
	UB9GH	—	1 1/4"	48"	1	—		
	UB9CG	—	1 1/4"	24"	1	—		
	UB9DG	—	1 1/4"	36"	1	—		
	UB9HG	—	1 1/4"	48"	1	—		
	UB9CH	—	1 1/2"	18"	1	—		
	UB9DH-UPC	UB9DHB	1 1/2"	24"	1	1		
	UB9FH	—	1 1/2"	36"	1	—		
	UB9HH	—	1 1/2"	48"	1	—		
	UB9CJ	—	2"	18"	1	—		
	UB9D-UPC	UB9DJB	2"	24"	1	1		
	UB9FJ	UB9FJB	2"	36"	1	1		
	UB9JU	—	2"	48"	1	—		
	UB9CK	—	2 1/2"	18"	1	—		
	UB9DK-UPC	UB9DKB	2 1/2"	24"	1	1		
	UB9FK	UB9FKB	2 1/2"	36"	1	1		
	UB9HK	—	2 1/2"	48"	1	—		
	UB9CL	—	3"	18"	1	—		
	UB9DL	UB9DLB	3"	24"	1	1		
	UB9FL	UB9FLB	3"	36"	1	1		
	UB9HL	—	3"	48"	1	—		
	UB9DN	UB9DNB	4"	24"	1	1		
	UB9FN	UB9FNB	4"	36"	1	1		
	UB9HN	UB9HNB	4"	48"	1	1		
	UB9NN	—	4"	120"	1	—		
	UB9PP	—	5"	36"	1	—		
	UB9HP	—	5"	48"	1	—		
	UB9JP	—	5"	60"	1	—		
	UB9FR	—	6"	36"	1	—		
	UB9HR	—	6"	48"	1	—		
	UB9JR	—	6"	60"	1	—		
	45° Elbow 	UB7CF	—	1"	18"	1	—	
		UB7DF	—	1"	24"	1	—	
		UB7FF	—	1"	36"	1	—	
UB7HF		—	1"	48"	1	—		
UB7DG		—	1 1/4"	24"	1	—		
UB7FG		—	1 1/4"	36"	1	—		
UB7HG		—	1 1/4"	48"	1	—		
UB7CH		—	1 1/2"	18"	1	—		
UB7DH		UB7DHB	1 1/2"	24"	1	1		
UB7FH		—	1 1/2"	36"	1	—		
UB7HH		—	1 1/2"	48"	1	—		
UB7CJ		—	2"	18"	1	—		
UB7DJ		UB7DJB	2"	24"	1	1		
UB7FJ		UB7FJB	2"	36"	1	1		
UB7JU		—	2"	48"	1	—		
UB7DK		UB7DKB	2 1/2"	24"	1	1		
UB7FK		—	2 1/2"	36"	1	—		
UB7HK		—	2 1/2"	48"	1	—		
UB7CL		—	3"	18"	1	—		
UB7DL		UB7DLB	3"	24"	1	1		
UB7FL		UB7FLB	3"	36"	1	1		
UB7HL		—	3"	48"	1	—		
UB7DN		UB7DNB	4"	24"	1	1		
UB7FN		UB7FNB	4"	36"	1	1		
UB7HN		—	4"	48"	1	—		
UB7FP		—	5"	36"	1	—		
UB7HP		—	5"	48"	1	—		
UB7FR		—	6"	36"	1	—		
UB7HR		—	6"	48"	1	—		
UB7JR		—	6"	60"	1	—		
30° Elbow		UB6FN	—	4"	36"	1	—	
		UB6FR	—	6"	36"	1	—	
		22 1/2° Elbow 	—	UB5DHB	1 1/2"	24"	—	20
			—	UB5DJB	2"	24"	—	20
			—	UB5FJB	2"	36"	—	25
			—	UB5DKB	2 1/2"	24"	—	15
UB5DL	UB5DLB		3"	24"	1	10		
—	UB5FLB		3"	36"	—	10		
UB5DN	UB5DNB	4"	24"	1	5			
—	UB5FNB	4"	36"	—	1			
UB5FP	—	5"	36"	1	—			
11 1/4° Elbow	UB3FP	—	5"	36"	1	—		

www.carlon.com

Gross Automation (877) 268-3700 · www.carlonsales.com · sales@grossautomation.com