



# VERSAtile Aluminum Compression Terminal 500 MCM AL/CU; 3/8" pad bolt diameter; single hole

by ANDERSON  
Catalog ID: VCELO5038H1

VERSAtile Aluminum Compression Terminal 500 MCM AL/CU- 3/8" pad bolt diameter- single hole

- CSA certified, UL Listed for both concentric and compact aluminum and concentric copper conductor



\* Representative image

## Product Details

### General

Crimp Method	VERSAtile™ (Accommodates Conventional And Anderson Tools)
Material	Aluminum Alloy - Tin Plated
Material - Body	Aluminum
Number of Pad Holes	1
Number of Spade Holes	1
Plating Type	Tin
Style	Impact Extruded
UPC	096359336518

### Dimensions

Bolt Diameter	0.380 in
Diameter - Pad Bolt	0.38 in
Length Before Compression	0 in
Weight	0.196 lb

### Conductor Related

Conductor Compatibility	ACSR-Quail-2/0-6/1;ACSR-Pigeon-3/0-6/1;ACSR-Penguin-4/0-6/1;ACSR-Waxwing-266.8-18/1;ACSR-Partridge-266.8-26/7;ACSR-Ostrich-300-26/7;ACSR-Merlin-336.4-18/1;ACSR-Linnet-336.4-26/7;ACSR-Oriole-336.4-30/7;ACSR-Chickadee-397.5-18/1;ACSR-Brant-397.5-24/7;ACSR-Ibis-397.5-26/7;ACSR-Lark-397.5-30/7;ACSR-Brahma-203.2-16/19;AAC-Aster-2/0-7;AAC-Phlox-3/0-7;AAC-Oxlip-4/0-7;AAC-Valerian-250-19;AAC-Laurel-266.8-19;AAC-Tulip-336.1-19;AAC-Daffodil-350-19;AAC-Canna-397.5-19;AAC-Cosmos-477-19;AAC-Syringa-477-37;AAC-Zinnia-500-19;AAC-Hyacinth-500-37;AAAC 6201 Alloy-Anaheim-155.4-6/18;AAAC 6201 Alloy-Amherst-195.7-6/18;AAAC 6201 Alloy-Alliance-246.9-6/18
Conductor Diameter (Die Type Tooling) - Maximum	0.813 in
Conductor Diameter (Die Type Tooling) - Minimum	0.811 in
Conductor Diameter (VersaCrimp) - Maximum	0.813 in

Conductor Diameter (VersaCrimp) - Minimum	0.414 in
Lug Conductor Type	<ul style="list-style-type: none"><li>• AL</li><li>• CU</li></ul>

### Certifications and Compliance

UL Listed	Yes
-----------	-----

### Logistics

Carton Quantity	96 EA
-----------------	-------

**For further technical assistance, please contact us**

#### **Domestic Customer Service**

Hubbell Power Systems  
210 N. Allen Centralia, MO 65240 USA  
Phone: (573) 682-5521  
Fax: (573) 682-8475  
Email: [hpscsc@hubbell.com](mailto:hpscsc@hubbell.com)

#### **International Customer Service**

Phone: +1-573-682-5521  
Fax: +1-573-682-8516  
Email: [hpsintlcs@hubbell.com](mailto:hpsintlcs@hubbell.com)