



# TS-400 Digital Time Switch



PROJECT

LOCATION/TYPE

## Product Overview

### Description

The IntelliSwitch TS-400 series digital time switches automatically turn lights off after a preset time. The simple pushbutton operation provides users with convenient time out lighting control without the nuisance of twist timers.

### Operation

The TS replaces an existing wall switch. The TS-400 operates between 100 and 300 volts. Pressing the TS's on/off button turns lights on. The lights will remain on for the duration of the time-out setting which is adjustable from 5 minutes to 12 hours. Lights can be turned off before the time-out setting expires by pressing the on/off button. Also, the unit can be reset at any time by holding down the on/off button for 2 seconds. This will bring the timer back to its original time out setting and restart the countdown.

### Time Scroll Overrides

The time scroll option allows users to temporarily override the time out setting without adjusting the settings. Time scroll is selected with the calibration button. With time scroll programmed to "UP", lights can be held on longer than the time out period. With time scroll programmed to down "DN", lights can be turned off sooner than the time out period. Pressing the on/off switch for more than 4 seconds causes the timer to scroll in the set direction throughout the possible time out settings.

### Applications

The TS is an ideal lighting control choice in equipment rooms, storage areas, and closets.

## Features

- Time-out settings range from 5 minutes to 12 hours for flexibility in fitting many applications
- Optional flash and beep warnings allow time to reset the switch if someone is present
- Time scroll option provides temporary override of the preset time out period
- Simple reset feature for returning the switch to its original preset time-out setting
- Electroluminescent back-lit LCD shows timer countdown
- Terminal style wiring simplifies installation
- Zero crossing reduces stress on the relay and increases product longevity
- Pushbutton programming gives the TS an easy set up process
- Setting the time-out for 2 hours and time scroll to down allows Title 24 compliance for using override switches




# Specifications


- TS-400: Universal 120/230/277 VAC; 50/60 Hz
- Time-out adjustments range from 5 minutes to 12 hours (5 minute increments to 1 hour, then 15 minute increments to 12 hours)
- Optional visual warning: flashes lights at 5 minutes and 1 minute prior to time-out
- Optional audible warning: beeps every 5 seconds at 1 minute prior to time-out
- No minimum load requirement
- Compatible with all electronic ballasts and motor loads
- Dimensions: 2.66" x 1.79" x 1.76" (67.5mm x 45.5mm x 44.7mm)
- UL and CUL listed; Five year warranty

## Controls & Installation

### Product Controls




### Installation




## Wiring

### TS-400 Single Level Lighting



### TS-400 3-Way Lighting



## Ordering Information

Catalog No.	Color	Voltage	Load Requirement
<input type="checkbox"/> TS-400-W	White	120 VAC; 50/60 Hz or 230/277 VAC; 50/60 Hz	0-800 Watt ballast or 0-1200 Watt ballast
<input type="checkbox"/> TS-400-I	Ivory		
<input type="checkbox"/> TS-400-A	Lt. Almond		
<input type="checkbox"/> TS-400-B	Black		
<input type="checkbox"/> TS-400-G	Grey		

One ASP-211 single-gang cover plate included. Order ASP-422 for blank 2-gang cover plate, ASP-432 for 2-gang cover plate with switch option (specify color).