

Please Note:

Use the Product Drawing for all design activity

Product Type Features

Product Type	Heat Shrinkable Tubing
Color	Black

Mechanical Attachment

Adhesive	Without
----------	---------

Dimensions

Application Use Range (mm [in])	9 – 29.5 [0.354 – 1.161]
Expanded ID, Min. (mm [in])	33.00 [1.2992]
Recovered ID, Max. (mm [in])	8.00 [0.315]
Length (mm [in])	1200.00 [47.244]

Body Features

Product Name	WCSM
Pliancy	Semirigid
Wall Style	Heavy
Wall Type	Dual
Lining Type	Encapsulant
Material	Polymer
Shrink Ratio	4:1
Fluid Type	Brake Fluid, Water
Resistant To	Fluids, Mechanical Damage
Wall Thickness - Full Recovery (Nominal) (mm [in])	3.20 [0.1259]

Housing Features

Material Systems	No
------------------	----

Configuration Features

Conductor (Wire) Size	#4 - 4/0
-----------------------	----------

Industry Standards

Government/Industry Qualification	No
Flammability Rating	Non-Flame-Retardant
UL Rating	Recognized
CSA Certified	Yes
Approved Standards	None
RoHS/ELV Compliance	RoHS compliant, ELV compliant
Lead Free Solder Processes	Not relevant for lead free process
RoHS/ELV Compliance History	Always was RoHS compliant

Printer/Label Features

Voltage Rating (kV)	1
---------------------	---

Environmental

Fluid Resistance	Immersion
------------------	-----------

Conditions for Usage

High Temperature Compatible	No
-----------------------------	----

Operation/Application

Emission Free	No
Product Use	Power Cables
Application	Cable Jacketing, Insulation and Protection, Sealing, Underground Applications

Packaging Features

Packaging Method	Piece
------------------	-------

Product Availability

Product Source	U.K., U.S.
----------------	------------

Other

Brand	Raychem
-------	---------