



THREE-PHASE

Foot Mount *continued*

HP	kW	RPM	NEMA Frame	Catalog Number	List Price	Mult. Symbol	Approx. Shipping Weight (lbs)	Service Factor	FL Amps @ High	FL Eff (%)	"C" Dimension (in)	Voltage (V)	Notes
15	11	3600	254T	01536XT3E254T	2,387	XT	347	1.15	16.9	91.7	23.175	208-230/460	
		3600	254T	01536XT3H254T	2,387	XT	346	1.15	13.5	91.7	23.175	575	
		1800	254T	01518XT3E254T	2,653	XT	307	1.15	18.4	92.4	23.175	208-230/460	
		1800	254T	01518XT3H254T	2,653	XT	307	1.15	14.7	92.4	23.175	575	
		1200	284T	01512XT3E284T	4,048	XT	496	1.15	17.5	91.7	26.407	208-230/460	
		1200	284T	01512XT3H284T	4,048	XT	496	1.15	14.0	91.7	26.407	575	
		900	286T	01509XP3E286T	5,677	X1	530	1.15	19.0	88.5	27.905	208-230/460	30
		900	286T	01509XT3E286T	7,102	XT	535	1.15	19.0	91.0	27.905	208-230/460	
20	15	3600	256T	02036XT3E256T	3,083	XT	375	1.15	23.1	91.7	24.923	208-230/460	
		3600	256T	02036XT3H256T	3,083	XT	374	1.15	18.5	91.7	24.923	575	
		1800	256T	02018XT3E256T	3,008	XT	388	1.15	25.0	93.0	24.923	208-230/460	
		1800	256T	02018XT3H256T	3,008	XT	388	1.15	20.0	93.0	24.923	575	
		1200	286T	02012XT3E286T	4,444	XT	538	1.15	24.2	91.7	27.905	208-230/460	
		1200	286T	02012XT3H286T	4,444	XT	509	1.15	19.4	91.7	27.905	575	
		900	324T	02009XP3E324T	6,984	X1	631	1.15	28.0	89.5	29.602	208-230/460	30
		900	324T	02009XT3E324T	8,390	XT	653	1.15	27.5	92.4	29.602	208-230/460	
25	18.5	3600	284TS	02536XT3E284TS	4,188	XT	490	1.15	28.6	92.4	25.033	208-230/460	
		3600	284TS	02536XT3H284TS	4,188	XT	489	1.15	22.9	92.4	25.033	575	
		1800	284T	02518XT3E284T	3,886	XT	498	1.15	29.9	93.6	26.407	208-230/460	
		1800	284T	02518XT3H284T	3,886	XT	497	1.15	23.9	93.6	26.407	575	
		1200	324T	02512XT3E324T	5,375	XT	675	1.15	30.4	93.0	29.602	208-230/460	
		1200	324T	02512XT3H324T	5,375	XT	676	1.15	24.3	93.0	29.602	575	
		900	326T	02509XP3E326T	8,513	X1	691	1.15	35.5	89.5	31.106	208-230/460	30
		900	326T	02509XT3E326T	10,512	XT	720	1.15	35.4	92.4	31.106	208-230/460	
30	22	3600	286TS	03036XT3E286TS	4,262	XT	538	1.15	33.7	93.0	26.531	208-230/460	
		3600	286TS	03036XT3H286TS	4,262	XT	540	1.15	27.0	93.0	26.531	575	
		1800	286T	03018XT3E286T	4,296	XT	537	1.15	36.0	93.6	27.905	208-230/460	
		1800	286T	03018XT3H286T	4,296	XT	536	1.15	28.8	93.6	27.905	575	
		1200	326T	03012XT3E326T	6,196	XT	738	1.15	36.7	93.0	31.106	208-230/460	
		1200	326T	03012XT3H326T	6,196	XT	703	1.15	29.4	93.0	31.106	575	
		900	364/5T	03009XP3E364T	11,677	X1	1002	1.15	38.4	91.0	33.701	208-230/460	30
		900	364/5T	03009XT3E364T	15,071	XT	1011	1.15	38.5	93.0	33.701	208-230/460	
40	30	3600	324TS	04036XT3E324TS	5,583	XT	662	1.15	45.8	93.6	28.102	208-230/460	
		3600	324TS	04036XT3H324TS	5,583	XT	662	1.15	36.6	93.6	28.102	575	
		1800	324T	04018XT3E324T	5,380	XT	699	1.15	48.2	94.1	29.602	208-230/460	
		1800	324T	04018XT3H324T	5,380	XT	698	1.15	38.6	94.1	29.602	575	
		1200	364/5T	04012XT3E364T	10,576	XT	1082	1.15	47.1	94.1	33.701	208-230/460	
		1200	364/5T	04012XT3H364T	10,576	XT	1080	1.15	37.7	94.1	33.701	575	
		900	364/5T	04009XP3E365T	12,326	X1	1094	1.15	52.4	91.0	33.701	208-230/460	30
		900	364/5T	04009XT3E365T	15,505	XT	1110	1.15	52.2	93.6	33.701	208-230/460	

Continued on next page

Refer to electrical and mechanical data sections for additional technical information. Please refer to back cover for description of "NOTES"

For detailed specifications, data sheets, drawings and performance curves visit <http://catalog.wegelectric.com>

Data subject to change without notice.



THREE-PHASE

Foot Mount *continued*

HP	kW	RPM	NEMA Frame	Catalog Number	List Price	Mult. Symbol	Approx. Shipping Weight (lbs)	Service Factor	FL Amps @ High	FL Eff (%)	"C" Dimension (in)	Voltage (V)	Notes
50	37	3600	326TS	05036XT3E326TS	6,582	XT	723	1.15	55.5	94.1	29.606	208-230/460	
		3600	326TS	05036XT3H326TS	6,582	XT	723	1.15	44.4	94.1	29.606	575	
		1800	326T	05018XT3E326T	6,545	XT	730	1.15	60.6	94.5	31.106	208-230/460	
		1800	326T	05018XT3H326T	6,545	XT	728	1.15	48.5	94.5	31.106	575	
		1200	364/5T	05012XT3E365T	10,597	XT	1109	1.15	58.1	94.1	33.701	208-230/460	
		1200	364/5T	05012XT3H365T	10,597	XT	1044	1.15	46.5	94.1	33.701	575	
		900	404/5T	05009XP3E404T	14,420	X1	1674	1.15	64.9	91.7	38.074	208-230/460	30
		900	404/5T	05009XT3E404T	22,443	XT	1342	1.15	68.0	93.6	38.074	208-230/460	
60	45	3600	364/5TS	06036XT3E364TS	9,988	XT	1113	1.15	68.3	94.1	31.575	208-230/460	
		3600	364/5TS	06036XT3H364TS	9,988	XT	1108	1.15	54.6	94.1	31.575	575	
		1800	364/5T	06018XT3E364T	10,460	XT	1107	1.15	68.3	95.0	33.701	208-230/460	
		1800	364/5T	06018XT3H364T	10,460	XT	1102	1.15	54.6	95.0	33.701	575	
		1200	404/5T	06012XT3E404T	13,196	XT	1270	1.15	70.4	94.5	38.074	208-230/460	
		1200	404/5T	06012XT3H404T	13,196	XT	1222	1.15	56.3	94.5	38.074	575	
		900	404/5T	06009XP3E405T	16,985	X1	1284	1.15	77.0	91.7	38.074	208-230/460	30
		900	404/5T	06009XT3E405T	26,900	XT	1287	1.15	75.9	93.0	38.074	208-230/460	
75	55	3600	364/5TS	07536XT3E365TS	11,285	XT	1108	1.15	82.4	94.1	31.575	208-230/460	
		3600	364/5TS	07536XT3H365TS	11,285	XT	1033	1.15	65.9	94.1	31.575	575	
		1800	364/5T	07518XT3E365T	11,125	XT	1108	1.15	83.2	95.4	33.701	208-230/460	
		1800	364/5T	07518XT3H365T	11,125	XT	1104	1.15	66.6	95.4	33.701	575	
		1200	404/5T	07512XT3E405T	13,836	XT	1320	1.15	87.0	94.5	38.074	208-230/460	
		900	444/5T	07509XP3E444T	21,094	X1	2180	1.15	90.5	93.0	43.797	208-230/460	30
		900	444/5T	07509XT3E444T	29,094	XT	1920	1.15	92.2	93.6	43.797	208-230/460	
		3600	404/5TS	10036XT3E405TS	12,999	XT	1294	1.15	110	95.0	35.074	208-230/460	
100	75	3600	404/5TS	10036XT3G405TS	12,999	XT	1214	1.15	110	95.0	35.074	460	
		3600	404/5TS	10036XT3H405TS	12,999	XT	1214	1.15	88.1	95.0	35.074	575	
		1800	404/5T	10018XT3E405T	14,206	XT	1312	1.15	113	95.4	38.074	208-230/460	
		1800	404/5T	10018XT3G405T	14,206	XT	1308	1.15	113	95.4	38.074	460	
		1800	404/5T	10018XT3H405T	14,206	XT	1307	1.15	90.4	95.4	38.074	575	
		1200	444/5T	10012XT3E444T	21,032	XT	2235	1.15	121	95.0	43.797	208-230/460	
		1200	444/5T	10012XT3G444T	21,032	XT	2225	1.15	121	95.0	43.797	460	
		900	444/5T	10009XP3E445T	25,321	X1	2223	1.15	123	93.0	43.797	208-230/460	30
		900	444/5T	10009XP3G445T	25,321	X1	2534	1.15	123	93.0	43.797	460	30
		900	444/5T	10009XT3E445T	31,191	XT	2061	1.15	125	94.1	43.797	208-230/460	
		900	444/5T	10009XT3G445T	31,191	XT	2061	1.15	125	94.1	43.797	460	

Continued on next page

Refer to electrical and mechanical data sections for additional technical information. Please refer to back cover for description of "NOTES"

For detailed specifications, data sheets, drawings and performance curves visit <http://catalog.wegelectric.com>

Data subject to change without notice.