

6300 FAMILY

★★★★
300 lbs. LOAD CAPACITY
Combined Weight of User and Materials
Type IA Duty Rating

★★★★ **PER SIDE**
300 lbs. LOAD CAPACITY
Combined Weight of User and Materials
Type IA Duty Rating

T6300 SERIES
Twin Stepladder

THE EDGE™

**Upgraded
Duty
Rating**

★★★★★
375 lbs. LOAD CAPACITY
Combined Weight of User and Materials
Type IAA Duty Rating

6300 SERIES
Stepladder

THE EDGE™

D6300-2 SERIES
Extension Ladder

WERNER®



Ladders designed for the professional.

Werner 6300 family

is a line of ladders truly designed with the professional in mind. All 6300s are constructed of heavy duty electrically non-conductive fiberglass rails and carry a Type IA duty rating. Regardless of what type of profession you're in - there's a 6300 that's perfect for the job.

★★★★
300lbs.
UL LISTED
 Combined Weight of User and Materials

Type IA Duty Rating
 *Models D6300-2 & D6340-2
 are for 2 person use only.
 Type I Duty Rating



Direct rung to rail connections. Twist-Proof® glue joints exclusive to ALFLO rung joints.



Shoe is slotted, allowing entire weight of ladder to rest on shoe pad.

Available in 16', 20', 24', 28', 32', 36' and 40' heights

D6300-2SERIES Extension Ladder



Tool-Tra-Top® with drill holsters, tool and paint can holders, and small parts tray



Plated steel spreaders positioned inside ladder rails for increased resistance to damage.

Available in 3', 4', 5', 6', 7', 8', 10' and 12' heights

T6300SERIES Twin Stepladder



★★★★
300lbs.
UL LISTED
 PER SIDE
 Combined Weight of User and Materials


Type IA Duty Rating



Upgraded Duty Rating

★★★★★
375lbs.
UL LISTED
 Combined Weight of User and Materials

Type IAA Duty Rating



Tool-Tra-Top® with drill holsters and convenient tray for tools



EDGE® (Energy Diffusing GEOMETRY) molded brace and foot pad provides enhanced bracing strength and increased protection against damage. Molded external rail shield helps protect against abrasion damage

Available in 3', 4', 5', 6', 7', 8', 10' and 12' heights

6300SERIES Stepladder

D6300-2SERIES Extension Ladder

RED non-conductive fiberglass side rails with non-irritating fabric outer mat which assures a smooth trouble-free surface even after weathering.

BLACK mar-resistant, molded end caps and end closures. Includes pre-pierced holes at top of fly for field installation of accessories.

Heavy duty aluminum pulley with 5/16" polypropylene rope.

T6300SERIES Twin Stepladder

RED non-conductive fiberglass side rails with non-irritating fabric outer mat assure a smooth trouble-free surface even after weathering.

BLACK Tool-Tra-Top® with drill holsters, tool and paint can holders, and small parts tray. Ideal for 2 people (1 person each side only).

Every rivet backed up by metal part or washer to protect fiberglass.

EDGE® (Energy Diffusing GEOMETRY) molded brace and foot pad combination provides enhanced bracing strength and increased protection against damage.

Molded external rail shields help protect against abrasion damage.

6300SERIES Stepladder

RED non-conductive fiberglass side rails with non-irritating fabric outer mat which assures a smooth trouble-free surface even after weathering.

BLACK molded Tool-Tra-Top® with drill holster and convenient tray for tools.

EDGE® (Energy Diffusing GEOMETRY) molded brace and foot pad combination provides enhanced bracing strength and increased protection against damage

Double riveted aluminum steps are deeply serrated for Traction-Tred®.



D6300-2SERIES EXTENSION LADDER

Specifications

Model	Total Length Sections	Max. Working Length	Approx. Cu. Ft. Per Unit	Approx. Shipping Wt. Lb.s
D6316-2	16'	13'	6.9	37.0
D6320-2	20'	17'	8.6	45.0
D6324-2	24'	21'	10.2	52.0
D6328-2	28'	25'	11.9	60.0
D6332-2	32'	29'	13.6	72.0
*D6336-2	36'	32'	15.2	81.0
*D6340-2	40'	35'	16.9	89.0

*Exception Model D6336-2 & D6340-2 are 250 Lbs. Load Capacity, Type I Duty Rating

Dimensions

Rails:	3 ⁵ / ₁₆ " wide
Flange:	1 ³ / ₁₆ " wide
Rungs:	1 ¹ / ₂ "
Fly Width:	16" outside rails
Base Width:	19" outside shoes

T6300SERIES TWIN STEPLADDER

Specifications

Model No.	Size	Approx. Width	Approx. Spread	Approx. Cu. Ft. Per Unit	Approx. Shipping Wt. Lbs.
T6304	4'	19 ⁷ / ₈ "	36"	4.8	20.0
T6305	5'	21 ⁵ / ₈ "	43"	6.5	24.0
T6306	6'	23 ³ / ₈ "	50"	8.4	28.0
T6308	7'	25 ¹ / ₈ "	57 ¹ / ₈ "	10.0	33.0
T6308	8'	26 ⁷ / ₈ "	64"	12.8	38.0
T6310	10'	30 ³ / ₈ "	78"	18.0	56.0
T6312	12'	33 ⁷ / ₈ "	92"	24.1	71.0

Dimensions

Top	8 ¹ / ₂ " x 13"
Steps:	3" wide
Rails:	3 ³ / ₈ " wide
Flange:	1 ³ / ₁₆ " wide

6300SERIES STEPLADDER

Specifications

Model No.	Size	Approx. Width	Approx. Spread	Approx. Cu. Ft. Per Unit	Approx. Shipping Wt. Lbs.
6304	4'	19 ⁷ / ₈ "	29"	3.0	16.0
6305	5'	21 ⁵ / ₈ "	35 ¹ / ₄ "	4.1	19.0
6306	6'	23 ³ / ₈ "	41 ¹ / ₄ "	5.3	22.0
6308	7'	25 ¹ / ₈ "	47 ¹ / ₂ "	6.6	26.0
6308	8'	26 ⁷ / ₈ "	53 ¹ / ₂ "	8.1	30.0
6310	10'	30 ³ / ₈ "	65 ⁷ / ₈ "	12.5	38.0
6312	12'	33 ⁷ / ₈ "	78 ¹ / ₄ "	15.0	48.0

Dimensions

Top:	5 ³ / ₄ " x 13"
Steps:	3" wide
Front Rails:	3 ¹ / ₈ " wide
Rear Rails:	1 ⁷ / ₈ " wide
Flange:	1 ³ / ₁₆ " wide



CORPORATE HEADQUARTERS

Werner Co. 93 Werner Road Greenville, PA 16125-9499
Tel. (724) 588-8600 FAX (724) 588-0315
www.wernerladder.com