



*** 22451**
Slimline Slide-On Lamp Holder
 Plunger Pedestal-Type
 Shallow End
 For T8 Lamps
 660 Watts Max., 1000 Volts



*** 22452**
Slimline Slide-On Lamp Holder
 Fixed Pedestal-Type
 Shallow End
 For T8 Lamps
 660 Watts Max., 1000 Volts



*** 22490**
Stationary End Lamp Holder
 For HO, VHO,
 SHO Lamps
 660 Watts Max., 1000 Volts



*** 22491**
Plunger End Lamp Holder
 For HO, VHO,
 SHO Lamps
 660 Watts Max., 1000 Volts



*** 22457**
Medium Bi-Pin Lamp Holder
Floating Action for U-Shape Lamps
 Low Profile Size
 20 Gauge
 660 Watts Max., 600 Volts



*** 22458**
Medium Bi-Pin Lamp Holder
Floating Action for U-Shape Lamps
 Low Profile Size
 Disconnect Feature Guards
 Against Electric Shock
 No. 18/20 Gauge
 660 Watts Max., 600 Volts



*** 22453**
Medium Bi-Pin Lamp Holder
 Low Profile Size
 660 Watts Max., 600 Volts
 T8/T12 Non Shunted



*** 22455**
Medium Bi-Pin Turn Type Lamp Holder
 Standard Size
 No. 20 Gauge
 Panel Mount
 660 Watts Max., 600 Volts



*** 22456**
Medium Bi-Pin Turn Type Lamp Holder
 Standard Size
 No. 18 Gauge
 Panel Mount
 660 Watts Max., 600 Volts



*** 22454**
Medium Bi-Pin Turn Type Lamp Holder
 Low Profile Size
 No. 18/20 Gauge
 Panel Mount, Captive
 Mount and Screw
 660 Watts Max., 600 Volts
 Non Shunted



Fluorescent Lamp Starters

- * 22560 - FS-2 - RoHS Compliant**
 14, 15 and 20 Watt Lamps
- * 22561 - FS-4**
 30 and 40 Watt Lamps
- * 22562 - FS-5 - RoHS Compliant**
 4, 6 and 8 Watt Lamps