




CALL YOUR WOODHEAD REPRESENTATIVE TODAY!

SEE PAGES 2-7




WATERTITE® RUBBER DEVICES




WATERTITE® PLUG



WATERTITE® CONNECTOR



WATERTITE® 50A PLUG AND CONNECTOR



WATERTITE® DUPLEX COVERPLATE

Face View	NEMA Configuration	Amps/Volts	Plug ¹	Connector ¹	Duplex Coverplate With Female Receptacle	Single Coverplate With Female Receptacle
2-POLE/3-WIRE						
	Non-NEMA Locking	50A/125V	CS63W61	CS63W60	—	CS69W60³
	Non-NEMA Locking	50A/125V	63W61	63W60	—	69W60³
	Non-NEMA Locking	50A/250V	CS82W65	CS82W64	—	69W64³
	Non-NEMA Locking	50A/250VDC/600VAC	37W63	37W62	—	69W62³
	Non-NEMA Locking	50A/480V	CS84W65	CS84W64	—	67W64³
3-POLE/3-WIRE						
	Non-NEMA	15A/125V/10A/250V	14W07	15W07	60W07DPLX	60W07
	Non-NEMA Locking	15A/125V/10A/250V	24W07	25W07	65W07DPLX	65W07
	Non-NEMA Locking	20A/125V/250V	26W08	27W08	—	67W08
	Non-NEMA Locking	20A/250V	26W08G	27W08G	—	—
	Non-NEMA Locking	30A/125V/250V	28W08	29W08	—	69W08

¹ For cable range and proper cord specifications, see pages 168–170.

³ 50 Amp receptacles have weather resistant enclosures only.

For dimensional information, see pages 117–118.

For extra-hard outdoor use, order Watertite® devices in UV resistant black, add "BLK" to the end of the Woodhead number.